


ClearClock™ | Ultra-Low Jitter & Power Optimized 3.2 x 2.5 mm XO



AX3



ESD Sensitive



3.2 x 2.5 x 1.0 mm
RoHS/RoHS II Compliant
MSL = 1


Features

- Exceptionally Low RMS Jitter: < 80fs Typ (150fs Max @ 156.25MHz)
- Available in industry standard frequencies between 100MHz and 200MHz
- Lowest power consumption in its class (16mA Typ LVDS @ 156.25MHz)
- ± 25 ppm stability over industrial operating temperature (-40 to +85°C)
- 3.3V, 2.5V, 1.8V supply voltage options
- LVPECL, LVDS, HCSL differential outputs
- Industry standard 3.2 x 2.5 x 1.0 mm footprint
- Available in Abracon's Global Distribution Network

Applications

- PCI Express
- 10G/40G/100G optical Ethernet
- Networking & communication
- RF systems, base stations (BTS)
- Data center
- Test & measurement

Options and Part Identification [Note 1]



Part Number Example:

AX3PAD1-156.2500T


Note 1: Contact Abracon for non-standard configurations and/or requests with carrier frequency callouts up to 5 & 6 digit accuracy after the decimal.



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 03.21.2019

ABRACON IS
ISO9001-2015
CERTIFIED



AX3



ESD Sensitive


 3.2 x 2.5 x 1.0 mm
 RoHS/RoHS II Compliant
 MSL = 1

Electrical Characteristics

Parameters			Min.	Typ.	Max.	Unit	Notes
Frequency Range			100		200	MHz	
Supply Voltage (V _{dd}) ^[Note 2]			2.97	3.3	3.63	V	Option A
			2.37	2.5	2.62		Option B
			1.71	1.8	1.89		Option C
Supply Current (I _{dd})	LVPECL		30	50	mA	Max. @ 200MHz; 3.3V	
	LVDS		16	27		Max. @ 200MHz; 3.3V	
	HCSL		17	30		Max. @ 200MHz; 3.3V	
Operating Temperature Range			-20		+70	°C	Option “D”
			-40		+85		Option “F”
Storage Temperature			-55		+150	°C	
Frequency Accuracy (Initial Set-Tolerance) at time of shipment (Pre-Reflow) @ +25°C			-10	< ±5	+10	ppm	Relative to carrier
Frequency Stability over Operating Temperature Range (Relative to Post Reflow Frequency)			-15		+15	ppm	Over -20°C to +70°C
			-25		+25		Over -40°C to +85°C
Aging over 20 Year Product Life ^[Note 3, 4]			-15		+15	ppm	
All-Inclusive Frequency Accuracy (Total Stability) over 20 Year Product Life ^[Note 3]			-40		+40	ppm	Over -20°C to +70°C
			-50		+50		Over -40°C to +85°C
Rise (Tr) / Fall (Tf) Time (20% to 80% V _{pp})				300	500	ps	20% to 80% V _{pp}
Duty Cycle			45		55	%	
Startup Time ^[Note 3]				< 2	5	ms	
Output High Voltage (V _{OH}) Output Low Voltage (V _{OL})	LVPECL	V _{OH}	V _{dd} -1.03		V _{dd} -0.60	V	50Ω to V _{dd} -2.0V or Thevenin equivalent
		V _{OL}	V _{dd} -1.85		V _{dd} -1.60		
	LVDS	V _{OH}		1.40	1.60		100Ω between OUT-P and OUT-N
		V _{OL}	0.9	1.10			
	HCSL	V _{OH}	0.66	0.74	0.85		50Ω to Ground
		V _{OL}	-0.15	0	0.15		
Output Enable & Disable Control			0.7*(V _{dd})			V	Output Enable; or No Connect
					0.3*(V _{dd})		Output Disable; High Impedance
Output Enable Time					10	ms	
Output Disable Time					0.2	μs	
Output Disable Current Consumption					< 10	μA	OE ≤ 0.3V
RMS Phase Jitter (12kHz-20MHz BW)				≤ 75	150	fs	@156.25MHz, 3.3V, LVPECL

Note 2: Supply Voltage (V_{dd}) = 1.8V option not available with LVPECL output

Note 3: Relative to initial measured frequency @ +25°C

Note 4: Includes temperature stability, initial frequency accuracy, load pulling, power supply variation, and 20 year aging



AX3



ESD Sensitive



3.2 x 2.5 x 1.0 mm
RoHS/RoHS II Compliant
MSL = 1

RMS Phase Jitter (12kHz -20MHz BW) | $V_{dd} = 3.3V$

Frequency (MHz)	Output	RMS Jitter	
		Typ. (fs)	Max (fs)
100	HCSL	153	200
	LVPECL	211	300
	LVDS	304	500
114.285	LVPECL	264	500
	LVDS	239	500
122.88	HCSL	122	200
	LVPECL	228	300
	LVDS	198	300
125	HCSL	138	200
	LVPECL	91	150
	LVDS	186	300
148.5	LVPECL	154	200
	LVDS	158	200
150	LVPECL	154	200
	LVDS	153	200
155.52	LVPECL	121	150
156.25	HCSL	113	150
	LVPECL	75	150
	LVDS	115	150
200	LVDS	70	150



AX3



ESD Sensitive




3.2 x 2.5 x 1.0 mm
RoHS/RoHS II Compliant
MSL = 1


Phase Noise Test Setup ^[Note 5]

- Keysight E5052B Signal Source Analyzer
- Integration Bandwidth = 12kHz to 20MHz
- Spurious Activity (entire plot trace) = Not Omitted (Normalized in dBc/Hz)
- Specified Spur Omission Function = Not Enabled
- IF Gain = 20dB
- Correlation = 5
- Average = 3


F=156.2500MHz | V_{dd}=3.3V | LVPECL
RMS Phase Jitter = 75 fs




F=156.2500MHz | V_{dd}=3.3V | HCSL
RMS Phase Jitter = 113 fs



F= 156.2500MHz | V_{dd}=3.3V | LVDS
RMS Phase Jitter = 115 fs



Note 5: Contact Abracon for phase noise plots at any desired combination of V_{dd}, differential output format, and carrier frequency within the available range



AX3




ESD Sensitive




3.2 x 2.5 x 1.0 mm
RoHS/RoHS II Compliant
MSL = 1

Representative Phase Noise Plots


F=100.0000MHz | V_{dd} =3.3V | LVPECL
RMS Phase Jitter = 211 fs




F= 100.0000MHz | V_{dd} =3.3V | LVDS
RMS Phase Jitter = 304 fs



F= 100.0000MHz | V_{dd} =3.3V | HCSL
RMS Phase Jitter = 153 fs



Note 5: Contact Abracon for phase noise plots at any desired combination of V_{dd} , differential output format, and carrier frequency within the available range



AX3




ESD Sensitive




3.2 x 2.5 x 1.0 mm
RoHS/RoHS II Compliant
MSL = 1

Representative Phase Noise Plots Continued


F=125.0000MHz | V_{dd}=3.3V | LVDS
RMS Phase Jitter = 186 fs




F= 125.0000MHz | V_{dd}=3.3V | HCSL
RMS Phase Jitter = 138 fs



F= 125.0000MHz | V_{dd}=3.3V | LVPECL
RMS Phase Jitter = 91 fs



Note 5: Contact Abracon for phase noise plots at any desired combination of V_{dd}, differential output format, and carrier frequency within the available range



AX3






ESD Sensitive



3.2 x 2.5 x 1.0 mm
RoHS/RoHS II Compliant
MSL = 1

Typical Frequency vs. Temperature Characteristics





AX3




ESD Sensitive




3.2 x 2.5 x 1.0 mm
RoHS/RoHS II Compliant
MSL = 1

Differential Output Waveform



$$\text{Duty Cycle} = \left(\frac{T_1}{T_2} \right) * 100\%$$



AX3




ESD Sensitive



3.2 x 2.5 x 1.0 mm
RoHS/RoHS II Compliant
MSL = 1


Recommended Test Circuit ^[Note 6]

LVPECL




$V_{dd}=3.3V$: $R1=R3=127\Omega$; $R2=R4=82.5\Omega$
 $V_{dd}=2.5V$: $R1=R3=250\Omega$; $R2=R4=62.5\Omega$


LVDS @ $V_{dd} = 3.3V$ & $2.5V$



HCSL



Note 6: Recommended test circuit images display OE Functions Option 1 & Option 2 where the OE Function is located on Pin 1
 When the OE Function is located on Pin 2, then Pin 1=No Connect & Pin 2=OE or No Connect



AX3




ESD Sensitive




3.2 x 2.5 x 1.0 mm
RoHS/RoHS II Compliant
MSL = 1


Mechanical Dimensions



TOP VIEW




BOTTOM VIEW



SIDE VIEW

Recommended Land Pattern




Pin #	Function
# 1	Option 1 & 2: [Note 7] Output Enable/Disable
# 2	Option 3 & 4: [Note 8] Output Enable/Disable
# 3	Ground
# 4	Output
# 5	Complementary output
# 6	Supply Voltage (V_{dd})

Note 7: Option 1 = Pin 1 OE Active HIGH;
Option 2 = Pin 1 OE Active LOW;

Note 8: Option 3 = Pin 2 OE Active HIGH;
Option 4 = Pin 2 OE Active LOW;

Dimensions: mm



AX3




ESD Sensitive



3.2 x 2.5 x 1.0 mm
RoHS/RoHS II Compliant
MSL = 1

Recommended Reflow Profile [Note 12]



Zone	Description	Temperature	Time
1	Preheat / Soak	$T_{SMIN} \sim T_{SMAX}$ $150^{\circ}C \sim 200^{\circ}C$	60 ~ 180 sec.
2	Reflow	T_L $217^{\circ}C$	60 ~ 150 sec.
3	Peak heat	T_P $260^{\circ}C \pm 5^{\circ}C$	20 ~ 40 sec.


Note 9: Ramp Up Rate ($T_L \rightarrow T_P$) = 3°C / sec. MAX

Note 10: Ramp Down Rate ($T_P \rightarrow T_L$) = 6°C / sec. MAX

Note 11: Time 25°C to Peak Temperature ($25^{\circ}C \rightarrow T_P$) = 8 minutes MAX

Note 12: Can withstand: 2 reflows

All temperatures refer to topside of the package, measured on the package body surface below.



AX3



ESD Sensitive



3.2 x 2.5 x 1.0 mm
RoHS/RoHS II Compliant
MSL = 1

Packaging


Blank = Bulk*

T = Tape & Reel 1,000 units/reel

T3 = Tape & Reel 3,000 units/reel

(* MOQ: 250 units)

Feeding (PULL) Direction →




Tape Dimensions

A	8.00
B	3.40
C	2.70
D	4.00
E	1.40
F	0.30
G	4.00
H	Ø1.55
I	1.75

Reel Dimensions

J	180.00
K	10.90
L	11.40
M	13.20
N	2.20
O	22.00



Dimensions: mm

ATTENTION: Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 03.21.2019

ABRACON IS
ISO9001-2015
CERTIFIED