

LDC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	BY	APP
		A		FIRST VERSION	17/02/2014	GF	SM

NOTES :

△ MATERIALS AND FINISH:

- HOUSING: PA66
- CONTACTS: COPPER ALLOY, FINISH: TIN OVER NICKEL UNDERPLATE
- SPRING: STAINLESS STRIP STEEL

2. MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)

3. WIRE TYPES AND SIZES ACCEPTED
WIRE RANGE: 20AWG~26AWG.
STRIP LENGTH: 9.5mm~10.5mm

4. PACKAGED IN TRAY.

5. CURRENT RATING: 6amp AC150V.

6. OPERATION TEMPERATURE: -40°C TO +105°C

P/N: *-2834015-*

COLOR CODE:





PIN No:

SERIES CODE

- | | |
|----------|----------|
| 1=GREEN | 2=2 POSN |
| 2=BLUE | 3=3 POSN |
| 3=BROWN | 4=4 POSN |
| 4=ORANGE | 5=5 POSN |
| 5=GREY | 6=6 POSN |
| 6=RED | 7=7 POSN |
| 7=YELLOW | 8=8 POSN |
| 8=PURPLE | |
| 9=WHITE | |
| 0=BLACK | |

REMARK: THE DIFFERENT COLORS COULD BE COMBINED
TO THE NEW CONNECTOR P/Ns FOR CUSTOMER REQUEST.

PCB Layout



DETAIL INNER

23.32	8 POSN
20.78	7 POSN
18.24	6 POSN
15.70	5 POSN
13.16	4 POSN
10.62	3 POSN
8.08	2 POSN
A	NO. OF POSITIONS

THIS DRAWING IS A CONTROLLED DOCUMENT.			
DESIGNED BY	INTEGRATED SERVICES	DATE	14JAN2015
CHKD BY	SHI XING	DATE	14JAN2015
APP'D BY	108-137079	DATE	11-4-137079
VERSION	1	DATE	11-4-137079
CUSTOMER DRAWING			
2.54mm Pitch Modular Screwless Conn.			
SIZE 1 CODE CODE DRAWING NO			
A2 00779 ©-2834015			
RESTRICTED TO			
SCALE 1:1			
SHEET 1 OF 1			
REV A			