

5.2mm × 20mm Time-Lag Ceramic Cartridge Fuse

multicompPRO

**RoHS
Compliant**



Specifications

Current Rating	: 15A
Voltage Rating	: 250V AC
Fuse Body Material	: Ceramic
Termination Material	: Nickel Plated Brass Caps
Operating Temperature	: -55°C to +125°C
Interrupting Current Rating	: 750 Amperes at 250V AC


Electrical Characteristics

Rating	100% Rating	135% Rating		200% Rating	
	Min.	Min.	Max.	Min.	Max.
15A	4Hrs.	-	1Hr.	2Sec.	120Sec

Part Number	Ampere Rating (A)	Voltage Rating (V)	Nominal Cold Resistance (Ohms)	Nominal Melting I ² t (A ² sec.)
MP000838	15	250	0.0041	534.24

UL Approved

Mechanical Dimensions



Part Number Table

Description	Part Number
Cartridge Fuse, Time-Lag, Ø5.2mm × 20mm, 15A, 250V AC	MP000838

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicompPRO