


Glass Passivated Rectifier Diodes

V_{RRM} - 200 Volts to 1000 Volts, 2A

multicompPRO



Features

- Low cost
- Low reverse leakage current
- Low forward voltage drop
- Fast switching for high efficiency
- High current capability
- Meet UL flammability classification 94V-0
- Lead free
- Case style: DO-204AC (DO-15) molded plastic

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

Characteristics	Symbol	FR203G	FR206G	FR207G	Unit
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	200	800	1000	V
Maximum RMS Voltage	V _{RMS}	140	560	700	
Maximum DC Blocking Voltage	V _{DC}	200	800	1000	
Maximum Average Forward Rectified Current @ T _A = 50°C	I _(AV)	2			A
Peak Forward Surge Current, 8.3mS Single Half Sine-Wave, Superimposed on Rated Load (JEDEC Method)	I _{FSM}	60			A
Peak Forward Voltage at 2A DC (Note1)	V _F	1.3			V
Maximum DC Reverse Current @T _J = 25°C at Rated DC Blocking Voltage @T _J = 100°C	I _R	5 100			μA
Maximum Reverse Recovery Time (Note 2)	T _{RR}	150	500		
Typical Junction Capacitance (Note3)	C _J	30	20		pF
Typical Thermal Resistance Junction to Ambient	R _{θJA}	25			°C/W
Operating Junction Temperature Range	T _J	-55 to +150			°C
Storage Temperature Range	T _{STG}	-55 to +150			°C


Notes:

1. 300μS pulse width, 2% duty cycle
2. Measured with I_F = 0.5A, I_R = 1A, I_{RR} = 0.25A
3. Measured at 1MHz and applied reverse voltage of 4V DC
4. The typical data above is for reference only

Newark.com/exclusive-brands
Farnell.com/exclusive-brands
Element14.com/exclusive-brands

**RoHS
Compliant**

DO-204AC (DO-15)



Dimensions : Inches (Millimetres)

multicompPRO

Glass Passivated Rectifier Diodes

V_{RRM} - 200 Volts to 1000 Volts, 2A

multicompPRO

Rating and Characteristic Curves

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Surge Current




Fig. 3 - Typical Junction Capacitance





Fig. 4 - Typical Forward Characteristics



Part Number Table

Description	Part Number
Rectifier Diode, 200V, 2A, DO-204AC (DO-15)	FR203G
Rectifier Diode, 800V, 2A, DO-204AC (DO-15)	FR206G
Rectifier Diode, 1kV, 2A, DO-204AC (DO-15)	FR207G

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands
Farnell.com/exclusive-brands
Element14.com/exclusive-brands

multicompPRO