

PCB terminal block - SPTA-THR 1,5/ 4-5,08 R44 - 1071204

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, nominal current: 13.5 A, pitch: 5.08 mm, number of positions: 4, connection method: Push-in spring connection, mounting: THR soldering, conductor/PCB connection direction: 45 °, color: black




The figure shows the 10-position version

Your advantages

- ✓ Time saving push-in connection, tools not required
- ✓ Defined contact force ensures that contact remains stable over the long term
- ✓ Intuitive use through colour coded actuation lever
- ✓ Angled connection enables multi-row arrangement on the PCB
- ✓ Designed for integration into the SMT soldering process



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 145 pc |
| Minimum order quantity | 145 pc |
| GTIN |  4 055626 771151 |
| GTIN | 4055626771151 |
| Weight per Piece (excluding packing) | 2.200 g |
| Custom tariff number | 85369010 |
| Note | Made to Order (non-returnable) |

Technical data

Item properties

| | |
|---------------------------|---------------------------|
| Brief article description | PCB terminal block |
| Range of articles | SPTA 1,5/...-THR |
| Pitch | 5.08 mm |
| Number of positions | 4 |
| Connection method | Push-in spring connection |
| Mounting type | THR soldering |

PCB terminal block - SPTA-THR 1,5/ 4-5,08 R44 - 1071204

Technical data

Item properties

| | |
|------------------|---|
| Number of levels | 1 |
|------------------|---|

Electrical parameters

| | |
|---------------|--------|
| Rated current | 13.5 A |
|---------------|--------|

Connection capacity

| | |
|--|---|
| Conductor cross section solid | 0.2 mm ² ... 1.5 mm ² (Conductor connection with open terminal point) |
| | 0.34 mm ² ... 1.5 mm ² (Push-in connection) |
| Conductor cross section flexible | without |
| Conductor cross section flexible, with ferrule without plastic sleeve | 0.25 mm ² ... 1.5 mm ² |
| Conductor cross section, flexible, with ferrule, with plastic sleeve | 0.25 mm ² ... 1.5 mm ² |
| 2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve | 0.5 mm ² ... 0.75 mm ² |
| Stripping length | 10 mm |

Material data - contact

| | |
|-------------------------|---|
| Note | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/ JEDEC JESD 201 |
| Contact material | Cu alloy |
| Surface characteristics | hot-dip tin-plated |

Material data - housing

| | |
|---|--------|
| Insulating material | LCP GF |
| Insulating material group | III |
| CTI according to IEC 60112 | 175 |
| Flammability rating according to UL 94 | V0 |
| Glow wire flammability index GWFI according to EN 60695-2-12 | 850 |
| Glow wire ignition temperature GWIT according to EN 60695-2-13 | 775 |
| Temperature for the ball pressure test according to EN 60695-10-2 | 125 °C |

Dimensions for the product

| | |
|-----------------------------|----------|
| Length [l] | 11.6 mm |
| Width [w] | 19.84 mm |
| Height [h] | 15.07 mm |
| Pitch | 5.08 mm |
| Height (without solder pin) | 12.47 mm |
| Solder pin [P] | 2.6 mm |

Dimensions for PCB design

| | |
|---------------|--------|
| Hole diameter | 1.1 mm |
|---------------|--------|

Packaging information

| | |
|----------------------------|-----------------|
| Type of packaging | 44 mm wide tape |
| Pieces per package | 145 |
| Denomination packing units | Pcs. |

PCB terminal block - SPTA-THR 1,5/ 4-5,08 R44 - 1071204

Technical data

Packaging information

| | |
|-----------------------------|--|
| [W] tape width | 44 mm |
| [A] coil diameter | 330 mm |
| [W2] coil overall dimension | 50.4 mm |
| Outer packaging type | Transparent-Bag |
| ESD level | (D) electrostatically conductive |
| Specification | DIN EN 61340-5-1 (VDE 0300-5-1): 2008-07 |

Processing notes

| | |
|---|--|
| Process | Reflow/wave soldering |
| Specification | Following IPC/JEDEC J-STD-020E:2014-12 |
| | Following IEC 61760-1:2006-04 |
| | Following IEC 60068-2-58:2015-03 |
| Moisture Sensitive Level | MSL 1 |
| Classification temperature T _c | 260 °C |
| Solder cycles in the reflow | 3 |

Ambient conditions

| | |
|---|---|
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Ambient temperature (assembly) | -5 °C ... 100 °C |
| Ambient temperature (operation) | -40 °C ... 100 °C (dependent on the derating curve) |

Termination and connection method

| | |
|--|---------------------|
| Test for conductor damage and slackening | IEC 60999-1:1999-11 |
| | Test passed |

Pull-out test

| | |
|--|--------------------------------------|
| Pull-out test | IEC 60999-1:1999-11 |
| | Test passed |
| Conductor cross section / conductor type / tensile force | 0.2 mm ² / solid / > 10 N |
| | 1.5 mm ² / solid / > 40 N |

Electrical tests

| | |
|---------------|--------|
| Rated current | 13.5 A |
|---------------|--------|

Air clearances and creepage distances

| | |
|---|-----------------------|
| Specification | IEC 60947-7-4:2013-08 |
| Rated insulation voltage (III/3) | 250 V |
| Minimum clearance - inhomogeneous field (III/3) | 3 mm |
| Minimum clearance - inhomogeneous field (III/2) | 3 mm |
| Minimum clearance - inhomogeneous field (II/2) | 3 mm |
| Minimum creepage distance value (III/3) | 4 mm |
| Minimum creepage distance value (III/2) | 3.2 mm |
| Minimum creepage distance value (II/2) | 4 mm |

PCB terminal block - SPTA-THR 1,5/ 4-5,08 R44 - 1071204

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 8.0 | 27440401 |
| eCl@ss 9.0 | 27440401 |

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC002643 |
| ETIM 6.0 | EC002643 |

Approvals

Approvals

Approvals

cULus Recognized

Ex Approvals

Approval details

| | | | |
|----------------------------|-------|---|-----------------|
| cULus Recognized | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | E60425-20061129 |
| | B | D | |
| Nominal voltage UN | 300 V | 300 V | |
| Nominal current IN | 10 A | 10 A | |
| mm ² /AWG/kcmil | 24-16 | 24-16 | |

Accessories

Accessories

Crimping tool

Crimping pliers - CRIMPFOX 6 - 1212034



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm² ... 6.0 mm², lateral entry, trapezoidal crimp

Screwdriver tools

PCB terminal block - SPTA-THR 1,5/ 4-5,08 R44 - 1071204

Accessories

Screwdriver - SZS 0,4X2,5 VDE - 1205037



Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip

Test plug terminal block

Test plugs - MPS-MT 1-S - 1944372



Test plug, consisting of 1.0 mm Ø test pin and 2.0 mm Ø socket

Accessories - MPS-MT 1-S4-B RD - 1982800



Accessories