

Item no.:	734-263
Product description:	HEADER RIGHT ANGLE SOLDER PIN, 1 X 1 MM / 0.039 X 0.039 IN 3 POLE PIN SPACING 3.81 MM / 0.15 IN 100% PROTECTED AGAINST MISMATING WITH CLOSED END MATING DIRECTION PARALLEL TO PCB



Produkt kann von Bild abweichen / product may differ

Packing unit 200 pieces

Product group	3 (Multi Conn. System)
Weight	0.893 g
Color	orange
pole count	3
Height	8.5 mm
Height	0.335 in
Width	13.52 mm
Width	0.532 in
Depth	10.3 mm
Depth	0.406 in
Pin spacing from	3.81 mm
Pin spacing from	0.15 in
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A
Pollution degree	2
Measured voltage EN	320 V

Measured shock voltage	2.5 kV
Current intensity EN	10 A
Material group	I
Contact material	Electrolytic copper (Ecu)
Contact surface	tin-plated



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
734-263	BV	11915/A0	250	10	0,5-1,5
734-263	CCA	NL5641	250	10	0,5-1,5
734-263	CSA	154112-1465035	300	10	28-14
734-263	DNV	E-9218	250	10	0,5-1,5
734-263	GL	17296-00HH	250	10	0,5-1,5
734-263	KEMA	2077592.02	250	10	0,5-1,5
734-263	LR	96/20035	250	10	0,5-1,5
734-263	RMR	11130002	250	10	0,5-1,5
734-263	UR	E45171	250	10	28-14
734-263	UR	E45172	300	10	

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected