

GSTB 3/ 3-ST-7,62

Order No.: 1750171

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=1750171>

Plug component, Nominal current: 20 A, Number of positions: 3,
Pitch: 7.62 mm, Connection method: Screw connection, Color: green,
Contact surface: Tin

Commercial data

EAN	 4 017918 028275
sales group	E072
Pack	50 Pcs.
Customs tariff	85369010
Gross weight in pieces	0.010223 KG
Net weight per piece	0.010223 KG

Product notes

WEEE/RoHS-compliant since:
01/01/2003



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions

Pitch	7.62 mm
-------	---------

General

Range of articles	GSTB 3
Rated voltage (III/3)	500 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	20 A
Nominal cross section	2.5 mm ²

Stripping length	8 mm
Number of positions	3
Screw thread	M3

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Minimum AWG according to UL/CUL	30
Maximum AWG according to UL/CUL	14

Certificates / Approvals



Certification

UL Recognized

Certifications applied for:

Certification Ex:

Accessories

Item	Designation	Description
Connector/Adapter		
0201731	MPS-IH BK	Insulating sleeve, Color: black
0201702	MPS-IH GN	Insulating sleeve, Color: green
0201676	MPS-IH RD	Insulating sleeve, Color: red
0201663	MPS-IH WH	Insulating sleeve, Color: white
0201744	MPS-MT	Test plugs, Color: silver
0201647	RPS	Reducing plug, Color: gray

General

1750142	CS-STB	Coding profile, for plugging into the coding ribs of the plug at a later date, insulating material, color: Red
---------	--------	--

Marking

1051993	B-STIFT	Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm
1401844	BN-ZB 7,5/WH:UNBEDRUCKT	Marker pin Zack strip, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Plug in, for terminal block width: 7.5 mm, Lettering field: 6 x 4 mm
1400052	BNB-ZB 7,5,LGS:FORTL.ZAHLEN	Marker pin Zack strip, Strip, white, labeled, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 991 - 1000, Mounting type: Plug in, for terminal block width: 7.5 mm, Lettering field: 6 x 4 mm

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;