

MSTBC 2,5/ 6-STZF-5,08 BD:1-6

Order No.: 1726693

<http://eshop.phoenixcontact.com.cn/phoenix/treeViewClick.do?UID=1726693>

Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V,
Number of positions: 6, Pitch: 5.08 mm, Connection method: Crimp
connection, Color: green

Commercial data

Pack	50 pcs.
Customs tariff	85366990
Gross weight in pieces	4.27 g

Product notes

WEEE/RoHS-compliant since:
2006-03-22



Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions

Pitch	5.08 mm
Dimension a	25.4 mm

General

Range of articles	MSTBC 2,5/...-STZF
Rated surge voltage (III/3)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (II/2)	4 kV
Rated voltage (III/3)	320 V
Rated voltage (III/2)	320 V

Rated voltage (U _I /2)	630 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	12 A
Nominal cross section	2.5 mm ²
Number of positions	6

Connection data

Conductor cross section stranded min.	0.5 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	14
Minimum AWG according to UL/CUL	20
Maximum AWG according to UL/CUL	14

Certificates



Certification

CSA, cULus Recognized, VDE Gutachten mit
Fertigungsüberwachung, CCA, IECCEB CB Scheme

Certifications applied for:

Certification Ex:

Address

Phoenix Contact China
No. 36 Phoenix Road - Jiangning Development Zone
211100 Nanjing, China
Phone 86-25-52121888
Fax 86-25-52121555
<http://www.phoenixcontact.com.cn>

PHOENIX CONTACT Middle East FZ LLC
Technical modifications reserved;