


# MCC 1/ 5-STZ-3,81 KMGY

Order No.: 1918719

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=1918719>Plug component, Nominal current: 8 A, Number of positions: 5, Pitch:  
3.81 mm, Connection method: Crimp connection, Color: light gray**Commercial data**

EAN	 4 017918 479589
Note	Made-to-order
sales group	E104
Pack	50 Pcs.
Customs tariff	85366990
Gross weight in pieces	0.001643 KG
Net weight per piece	0.001643 KG

**Product notes**WEEE/RoHS-compliant since:  
01/01/2003

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****Dimensions**

Pitch	3.81 mm
Dimension a	15.24 mm


**General**

Range of articles	MCC 1/...-STZ
Rated voltage (III/3)	160 V
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	8 A
Nominal cross section	1 mm <sup>2</sup>
Number of positions	5

**Connection data**

Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	1 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	18
Minimum AWG according to UL/CUL	20
Maximum AWG according to UL/CUL	18

**Certificates / Approvals**



Certification

cULus Recognized

Certifications applied for:

Certification Ex:

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact  
Technical modifications reserved;