

## MSTB 2,5/ 5-STF-5,08 ABGY AU

Order No.: 1882832

The illustration shows version MSTB 2,5/ 5-STF-5,08 AU



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1882832>

Plug component, Nominal current: 12 A, Nom. voltage: 250 V, Pitch:  
5.08 mm, Number of positions: 5, Connection type: Screw connection,  
Color: green

### Commercial data

|                |               |
|----------------|---------------|
| EAN            | 4017918354299 |
| Pack           | 50 pcs.       |
| Customs tariff | 85366990      |
| Weight/Piece   | 0.00968 KG    |

### Product notes

WEEE/RoHS-compliant since:  
01/01/2003



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Accessories

| Item | Designation | Description |
|------|-------------|-------------|
|------|-------------|-------------|

### Bridges

|         |          |                                                                                                       |
|---------|----------|-------------------------------------------------------------------------------------------------------|
| 1733172 | EBP 3- 5 | Insertion bridge, fully insulated, for plug connectors with 5.0 or 5.08 mm pitch, no. of positions: 3 |
|---------|----------|-------------------------------------------------------------------------------------------------------|

|         |          |                                                                                                       |
|---------|----------|-------------------------------------------------------------------------------------------------------|
| 1733185 | EBP 4- 5 | Insertion bridge, fully insulated, for plug connectors with 5.0 or 5.08 mm pitch, no. of positions: 4 |
| 1733198 | EBP 5- 5 | Insertion bridge, fully insulated, for plug connectors with 5.0 or 5.08 mm pitch, no. of positions: 5 |

#### General

|         |          |                                                                                                       |
|---------|----------|-------------------------------------------------------------------------------------------------------|
| 1733169 | EBP 2- 5 | Insertion bridge, fully insulated, for plug connectors with 5.0 or 5.08 mm pitch, no. of positions: 2 |
|---------|----------|-------------------------------------------------------------------------------------------------------|

#### Marking

|         |                          |                                                                                                                                                                                           |
|---------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1051993 | B-STIFT                  | Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm                                                                               |
| 0804293 | SK 5,08/3,8:FORTL.ZAHLEN | Marker card, printed horizontally, self-adhesive, 12 identical decades marked 1-10, 11-20 etc. up to 91-(99)100, sufficient for 120 terminal blocks                                       |
| 0805085 | SK 5,08/3,8:SO           | Marker card, special printing, self-adhesive, labeled acc. to customer requirements, 12 identical marker strips per card, max. 25-position labeling per strip, color: white               |
| 0803906 | SK U/3,8 WH:UNBEDRUCKT   | Unprinted marker cards, DIN A4 format, pitch as desired, self-adhesive, with 40 stamped marker strips, 185 mm strip length, can be labeled with the CMS system or manually with the M-PEN |
| 0811228 | X-PEN 0,35               | Marker pen without ink cartridge, for manual labeling of markers, labeling extremely wipe-proof, line thickness 0.35 mm                                                                   |

#### Plug/Adapter

|         |         |                                                                                                   |
|---------|---------|---------------------------------------------------------------------------------------------------|
| 1734634 | CP-MSTB | Keying profile, is inserted into the slot on the plug or inverted header, red insulating material |
|---------|---------|---------------------------------------------------------------------------------------------------|

#### Tools

|         |             |                                                                                                                                                      |
|---------|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1205053 | SZS 0,6X3,5 | Screwdriver, bladed, matches all screw terminal blocks up to 4.0 mm <sup>2</sup> connection cross section, blade: 0.6 x 3.5 mm, without VDE approval |
|---------|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------|

**Address**

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 00  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact  
Technical modifications reserved;