

## Feed-through header - GMSTBA 2,5/ 3-G - 1766356

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB headers, nominal current: 12 A, rated voltage (III/2): 630 V, number of positions: 3, pitch: 7.5 mm, color: green, contact surface: Tin, mounting: Wave soldering



The figure shows a 10-position version of the product

### Your advantages

- ✓ Maximum flexibility when it comes to device design – one header for connectors with different connection technologies
- ✓ Well-known mounting principle allows worldwide use
- ✓ Larger pitch for increased voltage requirements
- ✓ Closed contour for optimum stability of the plug-in connection



### Key Commercial Data

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| Packing unit | 250 pc                                                                               |
| GTIN         |  |
| GTIN         | 4017918032371                                                                        |

### Technical data

#### Dimensions

|                          |          |
|--------------------------|----------|
| Length [ l ]             | 12 mm    |
| Width                    | 22.5 mm  |
| Pitch                    | 7.5 mm   |
| Dimension a              | 15 mm    |
| Width [ w ]              | 22.5 mm  |
| Height [ h ]             | 12.1 mm  |
| Height                   | 8.6 mm   |
| Length of the solder pin | 3.5 mm   |
| Pin dimensions           | 1 x 1 mm |
| Length                   | 12 mm    |

#### General

# Feed-through header - GMSTBA 2,5/ 3-G - 1766356

## Technical data

### General

|                                        |                  |
|----------------------------------------|------------------|
| Range of articles                      | GMSTBA 2,5/...-G |
| Insulating material group              | I                |
| Rated surge voltage (III/3)            | 6 kV             |
| Rated surge voltage (III/2)            | 6 kV             |
| Rated surge voltage (II/2)             | 6 kV             |
| Rated voltage (III/3)                  | 400 V            |
| Rated voltage (III/2)                  | 630 V            |
| Rated voltage (II/2)                   | 630 V            |
| Connection in acc. with standard       | EN-VDE           |
| Nominal current $I_N$                  | 12 A             |
| Maximum load current                   | 12 A             |
| Insulating material                    | PA               |
| Flammability rating according to UL 94 | V0               |
| Color                                  | green            |
| Number of positions                    | 3                |

### Standards and Regulations


|                                        |        |
|----------------------------------------|--------|
| Connection in acc. with standard       | EN-VDE |
|                                        | CSA    |
| Flammability rating according to UL 94 | V0     |

### Environmental Product Compliance


|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Drawings

Drilling diagram



Dimensional drawing



## Approvals

### Approvals

## Feed-through header - GMSTBA 2,5/ 3-G - 1766356

### Approvals

#### Approvals

CSA / IEC EE CB Scheme / VDE Gutachten mit Fertigungsüberwachung / EAC / cULus Recognized

#### Ex Approvals

#### Approval details

|                    |                                                                                   |                                                                                                                                         |       |
|--------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------|
| CSA                |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | 13631 |
|                    | D                                                                                 | B                                                                                                                                       |       |
| Nominal voltage UN | 300 V                                                                             | 300 V                                                                                                                                   |       |
| Nominal current IN | 10 A                                                                              | 10 A                                                                                                                                    |       |

|                    |                                                                                     |                                                           |                |
|--------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|----------------|
| IECEE CB Scheme    |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | DE1-58978-B1B2 |
|                    |                                                                                     |                                                           |                |
| Nominal voltage UN | 400 V                                                                               |                                                           |                |
| Nominal current IN | 12 A                                                                                |                                                           |                |

|                                            |                                                                                     |                                                                                                                                                                                                                |          |
|--------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| VDE Gutachten mit<br>Fertigungsüberwachung |  | <a href="http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx">http://www2.vde.com/de/Institut/Online-Service/<br/>VDE-gepruefteProdukte/Seiten/Online-Suche.aspx</a> | 40004701 |
|                                            |                                                                                     |                                                                                                                                                                                                                |          |
| Nominal voltage UN                         | 400 V                                                                               |                                                                                                                                                                                                                |          |
| Nominal current IN                         | 12 A                                                                                |                                                                                                                                                                                                                |          |

|     |                                                                                     |  |         |
|-----|-------------------------------------------------------------------------------------|--|---------|
| EAC |  |  | B.01742 |
|-----|-------------------------------------------------------------------------------------|--|---------|

|                    |                                                                                     |                                                                                                                                                       |                 |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| cULus Recognized   |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-19931013 |
|                    | D                                                                                   | B                                                                                                                                                     |                 |
| Nominal voltage UN | 300 V                                                                               | 300 V                                                                                                                                                 |                 |
| Nominal current IN | 10 A                                                                                | 15 A                                                                                                                                                  |                 |

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>