



Printed-circuit board connector - PC 5/ 4-G-7,62 BK - 1769469

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB headers, nominal current: 41 A, number of positions: 4, pitch: 7.62 mm, color: black, contact surface: Tin, mounting: Wave soldering



Key Commercial Data

Packing unit	1
GTIN	 4 046356 447614
GTIN	4046356447614
Custom tariff number	85366930

Technical data

Dimensions

Pitch	7.62 mm
Dimension a	22.86 mm
Height	14.29 mm
Length of the solder pin	5 mm

General

Range of articles	PC 5/..-G
Rated voltage (III/3)	630 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	41 A
Color	black
Number of positions	4

Standards and Regulations

Connection in acc. with standard	EN-VDE
	CUL

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Printed-circuit board connector - PC 5/ 4-G-7,62 BK - 1769469

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC002637
ETIM 6.0	EC002637

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

EAC / cULus Recognized


Ex Approvals

Approval details

EAC		B.01742
-----	---	---------

Printed-circuit board connector - PC 5/ 4-G-7,62 BK - 1769469

Approvals

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E60425-19920722
	D	B	C
Nominal voltage UN	600 V	300 V	150 V
Nominal current IN	5 A	41 A	41 A