

PCB terminal block - SPT 16/ 1-V-10,0 WH - 1708575

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(<http://phoenixcontact.com/download>)



PCB terminal block, Number of positions: 1, Connection method: Push-in spring connection, Mounting: Wave soldering, Color: white

The figure shows the standard item



Key Commercial Data

Packing unit	1
GTIN	 4 055626 014074
Custom tariff number	85369010

Technical data

Dimensions

Pin dimensions	1,2 x 1 mm
Pin spacing	15 mm

General

Range of articles	SPT 16/...-V
Nominal cross section	16 mm ²
Solder pin surface	Sn
Number of positions	1

Classifications

eCl@ss

eCl@ss 5.1	27141190
eCl@ss 6.0	27261101

PCB terminal block - SPT 16/ 1-V-10,0 WH - 1708575

Classifications

eCl@ss

eCl@ss 8.0	27440401
eCl@ss 9.0	27440401

ETIM

ETIM 5.0	EC002643
----------	----------

Approvals

Approvals

Approvals

SEV / UL Recognized / cUL Recognized / IECCE CB Scheme / EAC / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

SEV	
mm²/AWG/kcmil	16
Nominal current I _N	76 A
Nominal voltage U _N	1000 V

UL Recognized 			
	B	C	D
mm²/AWG/kcmil	20-4	20-4	20-4
Nominal current I _N	66 A	66 A	10 A
Nominal voltage U _N	300 V	150 V	300 V

PCB terminal block - SPT 16/ 1-V-10,0 WH - 1708575

Approvals

cUL Recognized 			
	B	C	D
mm ² /AWG/kcmil	20-4	20-4	20-4
Nominal current I _N	66 A	66 A	10 A
Nominal voltage U _N	300 V	150 V	300 V

IECEE CB Scheme 	
Nominal current I _N	76 A
Nominal voltage U _N	1000 V


EAC

EAC

cULus Recognized 
--

Drawings

Drilling diagram



Dimensional drawing

