

# CB TM1 1A F1 P

Order No.: 2800858

The figure shows the CB TM1 0.5A F1 P version



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2800858>

Thermomagnetic device circuit breaker, 1-pos., tripping characteristic F1 (fast-blow), 1 PDT contact, plug for base element.

## Commercial data

|                          |                     |
|--------------------------|---------------------|
| EAN                      | 4 046356 690270     |
| sales group              | J712                |
| Pack                     | 1 Pcs.              |
| Customs tariff           | 85362010            |
| Gross weight in pieces   | 0.0423 KG           |
| Net weight per piece     | 0.0423 KG           |
| Catalog page information | Page 261 (C-6-2013) |

## Product notes

WEEE/RoHS-compliant since:  
06/22/2011



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General

|                                         |                                                                                                                     |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Installation instructions               | When mounted in rows, the nominal device current can be limited to just 80% or must be overdimensioned accordingly. |
| Inflammability class according to UL 94 | V0                                                                                                                  |
| Mounting type                           | On base element                                                                                                     |
| Color                                   | gray                                                                                                                |
| Number of positions                     | 1                                                                                                                   |

|                                                        |                                                                     |
|--------------------------------------------------------|---------------------------------------------------------------------|
| Insulating material group                              | II                                                                  |
| Pollution degree                                       | 2                                                                   |
| Type                                                   | Male                                                                |
| <b>Electrical data</b>                                 |                                                                     |
| Fuse type                                              | fast blow                                                           |
| Rated surge voltage                                    | 2.5 kV (Increased insulation in actuation area)                     |
| Rated voltage                                          | 240 V AC (U <sub>e</sub> according to IEC 60934)                    |
|                                                        | 277 V AC (UL 1077)                                                  |
|                                                        | 277 V AC (UL 508 - with plug-in base)                               |
|                                                        | 50 V DC (IEC 60934)                                                 |
|                                                        | 50 V DC (UL 1077)                                                   |
| Rated current I <sub>n</sub>                           | 50 V DC (UL 508 - with plug-in base)                                |
|                                                        | 1 A (IEC 60934)                                                     |
|                                                        | 1 A AC (inductive load according to UL 1077)                        |
|                                                        | 1 A DC (low-induction load according to UL 1077)                    |
|                                                        | 1 A AC (inductive load according to UL 508 - with plug-in base)     |
| Rated insulation voltage U <sub>i</sub>                | 1 A DC (low-induction load according to UL 508 - with plug-in base) |
|                                                        | 277 V AC (UL 1077)                                                  |
| Insulation resistance R <sub>iso</sub>                 | 250 V AC (IEC 60934)                                                |
|                                                        | > 100 MΩ (500 V DC)                                                 |
|                                                        |                                                                     |
| Auxiliary circuit                                      | 277 V AC / 0.5 A (Low-induction)                                    |
|                                                        | 277 V AC / 1 A (Low-induction, maximum of 2000 cycles)              |
|                                                        | 50 V DC / 1 A (Low-induction)                                       |
| Minimum auxiliary contact operating voltage            | 10 V                                                                |
| Maximum auxiliary contact operating voltage            | 240 V                                                               |
|                                                        | 240 V                                                               |
| Minimum auxiliary contact operating current            | 10 mA                                                               |
| Maximum auxiliary contact operating current            | 1 A                                                                 |
| Type of actuation                                      | S type                                                              |
| Tripping method                                        | TM (thermomagnetic)                                                 |
| Tripping level                                         | Trip-free mechanism (positive)                                      |
| Required backup fuse                                   | 15 A                                                                |
| Rated short-circuit switching capacity I <sub>cn</sub> | 300 A (240 V AC)                                                    |
|                                                        | 600 A (50 V DC)                                                     |

|                     |                                       |
|---------------------|---------------------------------------|
| Dielectric strength | 3000 V AC (Actuation area)            |
|                     | 1500 V AC (Main to auxiliary circuit) |
|                     | 1500 V AC (Open main circuit)         |
|                     | 1000 V AC (Open auxiliary circuit)    |
| Voltage drop        | 1.1 V (at 1 x I <sub>n</sub> )        |
| Cycles, max.        | 6000 (at 1 x I <sub>n</sub> )         |
| Contact type        | 1 PDT                                 |

#### Dimensions

|                        |         |
|------------------------|---------|
| Height                 | 45 mm   |
| Width                  | 12.3 mm |
| Depth                  | 52 mm   |
| Complete module height | 90 mm   |
| Complete module width  | 12.3 mm |
| Complete module depth  | 77.3 mm |

#### Ambient conditions

|                                         |                       |
|-----------------------------------------|-----------------------|
| Ambient temperature (operation)         | -30 °C ... 60 °C      |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C      |
| Degree of protection                    | IP30 (Actuation area) |

#### Standards and Regulations

|                          |                      |
|--------------------------|----------------------|
| Standards/specifications | EN 60934             |
|                          | UL 1077              |
|                          | UL 508               |
|                          | CSA 22.2 No. 235-041 |

#### Certificates / Approvals



Certification

cULus Recognized, VDE Zeichengenehmigung, GL

Certifications applied for:

Certification Ex:

## Accessories


| Item           | Designation       | Description                                                                                                                                                                                                         |
|----------------|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Bridges</b> |                   |                                                                                                                                                                                                                     |
| 2801014        | CB PT BRIDGE      | Bridge plug for bridging contacts 1 to 2 for CB base elements                                                                                                                                                       |
| 2801616        | CB RC BRIDGE      | Bridge plug for bridging contacts 11 to 14 for CB base elements                                                                                                                                                     |
| 3030336        | FBS 2-6           | Plug-in bridge, Number of positions: 2, Color: red                                                                                                                                                                  |
| 3030242        | FBS 3-6           | Plug-in bridge, Number of positions: 3, Color: red                                                                                                                                                                  |
| 3030255        | FBS 4-6           | Plug-in bridge, Number of positions: 4, Color: red                                                                                                                                                                  |
| 3030349        | FBS 5-6           | Plug-in bridge, Number of positions: 5, Color: red                                                                                                                                                                  |
| 3030271        | FBS 10-6          | Plug-in bridge, Number of positions: 10, Color: red                                                                                                                                                                 |
| 3030365        | FBS 20-6          | Plug-in bridge, Number of positions: 20, Color: red                                                                                                                                                                 |
| 3032224        | FBS 50-6          | Plug-in bridge, Number of positions: 50, Color: red                                                                                                                                                                 |
| <b>Marking</b> |                   |                                                                                                                                                                                                                     |
| 0825018        | ZBF 12 CUS        | Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, Mounting type: Snap into flat marker groove, for terminal block width: 12 mm, Lettering field: 5.15 x 12.15 mm |
| 0809735        | ZBF 12:UNBEDRUCKT | Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Snap into flat marker groove, for terminal block width: 12 mm, Lettering field: 5.15 x 12.15 mm                      |
| <b>Tools</b>   |                   |                                                                                                                                                                                                                     |
| 1212124        | CUTFOX-FBS        | <b>Cutting tool</b> , for separating individual jumper bars from FBS ... plug-in bridges and EB ... insertion bridges                                                                                               |

## Additional products


| Item                | Designation        | Description                                                                        |
|---------------------|--------------------|------------------------------------------------------------------------------------|
| <b>Base element</b> |                    |                                                                                    |
| 2801305             | CB 1/10-1/10 UT-BE | Base element with screw connection technology for CB... device circuit breakers    |
| 2800929             | CB 1/6-2/4 PT-BE   | Base element with push-in connection technology for CB ... device circuit breakers |

## Drawings

### Application drawing




### Diagram




Trigger characteristic in the DC range

### Dimensioned drawing



The figure shows the complete module consisting of a base element and connector



**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact  
Technical modifications reserved;