

REL-OR-230AC/2X21

Order No.: 2834261



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2834261>

Pluggable octal relay with power contacts, 2 PDT, test button,
mechanical switching position indication, coil voltage 230 V AC

Commercial data

EAN	 4 017918 941871
sales group	G082
Pack	10 Pcs.
Customs tariff	85364900
Gross weight in pieces	0.11456 KG
Net weight per piece	0.11456 KG
Catalog page information	Page 384 (C-7-2013)

Product notes

WEEE/RoHS-compliant since:
09/07/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions

Width	34.5 mm
Height	34.5 mm
Depth	52.5 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 60 °C
---------------------------------	------------------

Ambient temperature (storage/transport)	-40 °C ... 60 °C
---	------------------

Coil side

Nominal input voltage U_N	230 V AC
Typical input current at U_N	10 mA (at 50 Hz)
	11 mA (At 60 Hz)
Typical response time	5 ms ... 20 ms (AC, depending on phase relation)
Typical release time range	5 ms ... 20 ms (AC, depending on phase relation)
Coil resistance	6170 Ω $\pm$ 15 % (at 20 °C)

Contact side

Contact type	2 PDT
Contact material	AgSnIn
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	1 V
Maximum inrush current	on request
Min. switching current	10 mA
Limiting continuous current	10 A (N/O contact)
	5 A (N/C contact)
Interrupting rating (ohmic load) max.	2500 VA (for 250 V AC)


General

Test voltage relay winding/relay contact	2.5 kV AC (50 Hz, 1 min.)
Test voltage relay contact/relay contact	2.5 kV AC (50 Hz, 1 min.)
Operating mode	100% operating factor
Mechanical service life	10 x 10 ⁶ cycles
Standards/regulations	IEC 60664
Pollution degree	3
Surge voltage category	II
Mounting position	any
Assembly instructions	On relay base PR3

Connection data

Connection method	Plug connection
-------------------	-----------------

Certificates / Approvals



Certification

cULus Recognized

Certifications applied for:


Certification Ex:

Additional products


Item	Designation	Description
General		
2833602	PR3-BSC1/2X21	Relay socket PR3..., for octal relay REL-OR with 2 PDT, screw connections, connection facility for input/interference suppression modules, for mounting on NS 35/7.5

Drawings


Diagram



Interrupting rating




Electrical service life



Service life reduction factor with various cos phi

Circuit diagram



Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;