

## Relay Module - RIF-0-RPT-12DC/ 1 - 2903362

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Pre-assembled relay module with push-in connection, consisting of: relay base with ejector and power contact relay. Contact type: 1 N/O contact. Input voltage: 12 V DC



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 24.0 GRM |
| Custom tariff number                 | 85364110 |
| Country of origin                    | Germany  |

### Technical data

#### Note

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---------------------------------------------------------------------------|

#### Dimensions

|        |        |
|--------|--------|
| Width  | 6.2 mm |
| Height | 93 mm  |
| Depth  | 66 mm  |

#### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Ambient temperature (operation)         | -40 °C ... 60 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |

#### Coil side

|                                           |             |
|-------------------------------------------|-------------|
| Nominal input voltage $U_N$               | 12 V DC     |
| Input voltage range in reference to $U_N$ | see diagram |
| Typical input current at $U_N$            | 16 mA       |

# Relay Module - RIF-0-RPT-12DC/ 1 - 2903362

## Technical data

### Coil side

|                           |               |
|---------------------------|---------------|
| Typical response time     | 5 ms          |
| Typical release time      | 8 ms          |
| Operating voltage display | Yellow LED    |
| Protective circuit        | Damping diode |

### Contact side

|                                                        |                        |
|--------------------------------------------------------|------------------------|
| Contact type                                           | 1 N/O contact          |
| Contact material                                       | AgSnO                  |
| Maximum switching voltage                              | 250 V AC/DC            |
| Minimum switching voltage                              | 5 V (at 100 mA)        |
| Min. switching current                                 | 10 mA (at 12 V)        |
| Limiting continuous current                            | 6 A                    |
| Interrupting rating (ohmic load) max.                  | 140 W (at 24 V DC)     |
|                                                        | 20 W (at 48 V DC)      |
|                                                        | 18 W (at 60 V DC)      |
|                                                        | 23 W (at 110 V DC)     |
|                                                        | 40 W (at 220 V DC)     |
|                                                        | 1500 VA (for 250 V AC) |
| Switching capacity in acc. with DIN VDE 0660/IEC 60947 | 1 A (at 24 V, DC13)    |
|                                                        | 0.2 A (at 110 V, DC13) |
|                                                        | 0.1 A (at 220 V, DC13) |
|                                                        | 3 A (at 24 V, AC15)    |
|                                                        | 3 A (at 120 V, AC15)   |
|                                                        | 3 A (at 230 V, AC15)   |

### Connection data

|                                                                            |                      |
|----------------------------------------------------------------------------|----------------------|
| Connection method                                                          | Push-in connection   |
| Stripping length                                                           | 8 mm                 |
| Conductor cross section stranded min.                                      | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded max.                                      | 1.5 mm <sup>2</sup>  |
| Conductor cross section solid min.                                         | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.                                         | 1.5 mm <sup>2</sup>  |
| Conductor cross section stranded, with ferrule with plastic sleeve min.    | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule with plastic sleeve max.    | 1.5 mm <sup>2</sup>  |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 1.5 mm <sup>2</sup>  |
| Conductor cross section AWG/kcmil max                                      | 16                   |
| Conductor cross section AWG/kcmil min.                                     | 26                   |

## Relay Module - RIF-0-RPT-12DC/ 1 - 2903362

### Technical data

#### General

|                                          |                                     |
|------------------------------------------|-------------------------------------|
| Test voltage relay winding/relay contact | 4 kV <sub>rms</sub> (50 Hz, 1 min.) |
| Operating mode                           | 100% operating factor               |
| Degree of protection                     | IP20 (Relay socket)                 |
|                                          | RT III (Relay)                      |
| Mechanical service life                  | Approx. $2 \times 10^7$ cycles      |
| Standards/regulations                    | DIN EN 50178                        |
|                                          | IEC 62103                           |
| Rated insulation voltage                 | 250 V AC                            |
| Pollution degree                         | 2                                   |
| Surge voltage category                   | III                                 |
| Mounting position                        | any                                 |
| Assembly instructions                    | In rows with zero spacing           |

### Articles in set

Single relay - REL-MR- 12DC/21 - 2961150



Plug-in miniature power relay, with power contact, 1 PDT, input voltage 12 V DC

Relay socket - RIF-0-BPT/1 - 2901873



RIF-0... relay base, for miniature power relay with 1 N/O contact or solid-state relays of the same design, push-in connection, for mounting on NS 35/7,5

### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27371102 |
| eCl@ss 4.1 | 27371102 |
| eCl@ss 5.0 | 27371603 |
| eCl@ss 5.1 | 27371603 |
| eCl@ss 6.0 | 27371603 |

## Relay Module - RIF-0-RPT-12DC/ 1 - 2903362

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 7.0 | 27371603 |
| eCl@ss 8.0 | 27371603 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001456 |
| ETIM 4.0 | EC001456 |
| ETIM 5.0 | EC001437 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211917 |
| UNSPSC 7.0901 | 39121516 |
| UNSPSC 11     | 39121516 |
| UNSPSC 12.01  | 39121516 |
| UNSPSC 13.2   | 39121516 |

### Accessories

#### Accessories

##### Jumper

Plug-in bridge - FBS 2-6 - 3030336



Plug-in bridge, Number of positions: 2, Color: red

Plug-in bridge - FBS 3-6 - 3030242



Plug-in bridge, Number of positions: 3, Color: red

## Relay Module - RIF-0-RPT-12DC/ 1 - 2903362

### Accessories

Plug-in bridge - FBS 4-6 - 3030255



Plug-in bridge, Number of positions: 4, Color: red

---

Plug-in bridge - FBS 5-6 - 3030349



Plug-in bridge, Number of positions: 5, Color: red

---

Plug-in bridge - FBS 10-6 - 3030271



Plug-in bridge, Number of positions: 10, Color: red

---

Plug-in bridge - FBS 20-6 - 3030365



Plug-in bridge, Number of positions: 20, Color: red

---

Plug-in bridge - FBS 50-6 - 3032224



Plug-in bridge, Number of positions: 50, Color: red

---

## Relay Module - RIF-0-RPT-12DC/ 1 - 2903362

### Accessories

Plug-in bridge - FBS 2-6 BU - 3036932



Plug-in bridge, Number of positions: 2, Color: blue

---

Plug-in bridge - FBS 3-6 BU - 3036945



Plug-in bridge, Number of positions: 3, Color: blue

---

Plug-in bridge - FBS 4-6 BU - 3036958



Plug-in bridge, Number of positions: 4, Color: blue

---

Plug-in bridge - FBS 5-6 BU - 3036961



Plug-in bridge, Number of positions: 5, Color: blue

---

Plug-in bridge - FBS 10-6 BU - 3032198



Plug-in bridge, Number of positions: 10, Color: blue

---

## Relay Module - RIF-0-RPT-12DC/ 1 - 2903362

### Accessories

Plug-in bridge - FBS 20-6 BU - 3032208



Plug-in bridge, Number of positions: 20, Color: blue

---

Plug-in bridge - FBS 50-6 BU - 3032211



Plug-in bridge, Number of positions: 50, Color: blue

---

Plug-in bridge - FBS 2-6 GY - 3032237



Plug-in bridge, Number of positions: 2, Color: gray

---

Plug-in bridge - FBS 3-6 GY - 3032240



Plug-in bridge, Number of positions: 3, Color: gray

---

Plug-in bridge - FBS 4-6 GY - 3032279



Plug-in bridge, Number of positions: 4, Color: gray

---

## Relay Module - RIF-0-RPT-12DC/ 1 - 2903362

### Accessories

Plug-in bridge - FBS 5-6 GY - 3032266



Plug-in bridge, Number of positions: 5, Color: gray


Plug-in bridge - FBS 10-6 GY - 3032253



Plug-in bridge, Number of positions: 10, Color: gray


### Drawings

Circuit diagram



DC coils

Diagram




Operating voltage range




## Relay Module - RIF-0-RPT-12DC/ 1 - 2903362

Diagram




Diagram



Interrupting rating

Service life reduction factor

Diagram



Electrical service life