

PR3-BSC1/3X21

Order No.: 2833615



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2833615>

Relay socket PR3..., for octal relay REL-OR with 3 PDT, screw connections, connection facility for input/interference suppression modules, for mounting on NS 35/7.5

Commercial data

EAN	 4 017918 933838
sales group	G302
Pack	10 Pcs.
Customs tariff	85366990
Gross weight in pieces	0.06832 KG
Net weight per piece	0.0656 KG
Catalog page information	Page 383 (C-7-2013)

Product notes

WEEE/RoHS-compliant since:
01/01/2005



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions

Width	38 mm
Height	75 mm
Depth with retaining bracket	84 mm (EL3-M52)

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	14
2 conductors with same cross section, solid max.	2.50 mm ²
2 conductors with same cross section, stranded max.	2.50 mm ²
2 conductors with same cross section, AWG max.	14
Connection method	Screw connection
Stripping length	10 mm
Screw thread	M3

General

Nominal voltage U _N	400 V AC/DC
Nominal current I _N	10 A
Color	green

Certificates / Approvals



Certification

CSA, cULus Recognized

Certifications applied for:

Certification Ex:

Additional products

Item	Designation	Description
General		
2834287	REL-OR- 24AC/3X21	Pluggable octal relay with power contacts, 3 PDT, test button, mechanical switching position indication, coil voltage 24 V AC
2834274	REL-OR- 24DC/3X21	Pluggable octal relay with power contacts, 3 PDT, test button, mechanical switching position indication, coil voltage 24 V DC
2834290	REL-OR-120AC/3X21	Pluggable octal relay with power contacts, 3 PDT, test button, mechanical switching position indication, coil voltage 120 V AC
2834300	REL-OR-230AC/3X21	Pluggable octal relay with power contacts, 3 PDT, test button, mechanical switching position indication, coil voltage 230 V AC

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;