

## Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PLC-INTERFACE, consisting of DIN-rail-mountable basic terminal block in 14 mm with Push-in connection and plug-in relay with power contact, 2 changeover contacts, 230 V AC/220 V DC input voltage. Approved according to ATEX/IECEx (Zone 2) and Ex Zone Class I, Div. 2.



COMPLIANT

### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 10 pc                                                                                                   |
| Minimum order quantity               | 10 pc                                                                                                   |
| GTIN                                 | <br>4 055626 363196 |
| GTIN                                 | 4055626363196                                                                                           |
| Weight per Piece (excluding packing) | 64.760 g                                                                                                |
| Custom tariff number                 | 85364900                                                                                                |
| Country of origin                    | Germany                                                                                                 |
| Note                                 | Made to Order (non-returnable)                                                                          |

### Technical data

#### Note

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---------------------------------------------------------------------------|

#### Dimensions

|        |       |
|--------|-------|
| Width  | 14 mm |
| Height | 80 mm |
| Depth  | 94 mm |

#### Ambient conditions

|                                         |                                 |
|-----------------------------------------|---------------------------------|
| Ambient temperature (operation)         | -20 °C ... 60 °C (UL)           |
|                                         | -40 °C ... 55 °C (ATEX / IECEx) |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C                |
| Degree of protection                    | RT III (Relay)                  |
|                                         | IP20 (Relay base)               |

# Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

## Technical data

### Coil side

|                                         |                                   |
|-----------------------------------------|-----------------------------------|
| Nominal input voltage $U_N$             | 230 V AC                          |
|                                         | 220 V DC                          |
| Typical input current at $U_N$          | 4.5 mA ( $U_N = 230$ V AC)        |
|                                         | 4.3 mA ( $U_N = 220$ V DC)        |
| Typical response time                   | 7 ms                              |
| Typical release time                    | 10 ms                             |
| Protective circuit                      | Bridge rectifier Bridge rectifier |
| Operating voltage display               | Yellow LED                        |
| Power dissipation for nominal condition | 1.04 W                            |

### Contact side

|                                       |                                                                                                                                                                                                                                               |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Contact type                          | 2 PDT                                                                                                                                                                                                                                         |
| Type of switch contact                | Single contact                                                                                                                                                                                                                                |
| Contact material                      | AgNi                                                                                                                                                                                                                                          |
| Maximum switching voltage             | 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...) |
| Minimum switching voltage             | 5 V AC/DC (at 10 mA)                                                                                                                                                                                                                          |
| Min. switching current                | 10 mA (At 5 V)                                                                                                                                                                                                                                |
| Maximum inrush current                | 15 A (300 ms)                                                                                                                                                                                                                                 |
| Limiting continuous current           | 6 A                                                                                                                                                                                                                                           |
| Interrupting rating (ohmic load) max. | 140 W (at 24 V DC)                                                                                                                                                                                                                            |
|                                       | 85 W (at 48 V DC)                                                                                                                                                                                                                             |
|                                       | 60 W (at 60 V DC)                                                                                                                                                                                                                             |
|                                       | 44 W (at 110 V DC)                                                                                                                                                                                                                            |
|                                       | 60 W (at 220 V DC)                                                                                                                                                                                                                            |
|                                       | 1500 VA (for 250 V AC)                                                                                                                                                                                                                        |
| Switching capacity                    | 2 A (at 24 V, DC13)                                                                                                                                                                                                                           |
|                                       | 0.2 A (at 250 V, DC13)                                                                                                                                                                                                                        |
|                                       | 3 A (at 24 V, AC15)                                                                                                                                                                                                                           |
|                                       | 3 A (at 120 V, AC15)                                                                                                                                                                                                                          |
|                                       | 3 A (at 250 V, AC15)                                                                                                                                                                                                                          |

### General

|                                          |                           |
|------------------------------------------|---------------------------|
| Test voltage relay winding/relay contact | 4 kV AC (50 Hz, 1 min.)   |
| Test voltage PDT/PDT                     | 2.5 kV AC (50 Hz, 1 min.) |
| Operating mode                           | 100% operating factor     |
| Mechanical service life                  | $3 \times 10^7$ cycles    |
| Mounting position                        | any                       |
| Assembly instructions                    | In rows with zero spacing |

### Connection data

# Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

## Technical data

### Connection data

|                                  |                                                              |
|----------------------------------|--------------------------------------------------------------|
| Connection name                  | Coil side                                                    |
| Connection method                | Push-in connection                                           |
| Stripping length                 | 8 mm                                                         |
| Conductor cross section solid    | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                 |
| Conductor cross section flexible | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                 |
|                                  | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (Single ferrule) |
|                                  | 2x 0.5 mm <sup>2</sup> ... 1 mm <sup>2</sup> (TWIN ferrule)  |
| Conductor cross section AWG      | 26 ... 14                                                    |

### Connection data 2

|                                  |                                                              |
|----------------------------------|--------------------------------------------------------------|
| Connection name                  | Contact side                                                 |
| Connection method                | Push-in connection                                           |
| Stripping length                 | 8 mm                                                         |
| Conductor cross section solid    | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                 |
| Conductor cross section flexible | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                 |
|                                  | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (Single ferrule) |
|                                  | 2x 0.5 mm <sup>2</sup> ... 1 mm <sup>2</sup> (TWIN ferrule)  |
| Conductor cross section AWG      | 26 ... 14                                                    |

### Standards and Regulations

|                          |                                       |
|--------------------------|---------------------------------------|
| Designation              | Standards/regulations                 |
| Standards/regulations    | IEC 60664                             |
|                          | EN 50178                              |
|                          | EN 60079-0, -7, -15                   |
| Rated insulation voltage | 250 V AC                              |
| Rated surge voltage      | 6 kV                                  |
| Insulation               | Safe isolation, reinforced insulation |
| Pollution degree         | 2                                     |
| Overvoltage category     | III                                   |
| Conformance              | CE-compliant                          |
| ATEX                     | # II 3G Ex ec nC IIC T4 Gc            |
| IECEX                    | Ex ec nC IIC T4 Gc                    |
| UL, USA                  | Class I, Zone 2, AEx nA nC IIC T6     |
| UL, USA/Canada           | Class I, Div. 2, Groups A, B, C, D    |
| UL, Canada               | Class I, Zone 2, Ex nA nC IIC Gc T6 X |

### Conformance/approvals

|                |                            |
|----------------|----------------------------|
| Designation    | CE                         |
| Identification | CE-compliant               |
| Designation    | ATEX                       |
| Identification | # II 3G Ex ec nC IIC T4 Gc |
| Certificate    | IBExU16ATEXB015 X          |

## Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

### Technical data

#### Conformance/approvals

|                |                                       |
|----------------|---------------------------------------|
| Designation    | IECEX                                 |
| Identification | Ex ec nC IIC T4 Gc                    |
| Certificate    | IECEX IBE 16.0029X                    |
| Designation    | UL, USA                               |
| Identification | Class I, Zone 2, AEx nA nC IIC T6     |
| Designation    | UL, USA/Canada                        |
| Identification | Class I, Div. 2, Groups A, B, C, D    |
| Designation    | UL, Canada                            |
| Identification | Class I, Zone 2, Ex nA nC IIC Gc T6 X |


#### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

### Drawings

## Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

Diagram



Curve A


Maximum permissible continuous voltage  $U_{max}$  with limiting continuous current on the contact side (see relevant technical data)

Curve B

Minimum permissible operate voltage  $U_{op}$  after pre-excitation (see relevant technical data)

## Relay Module - PLC-RPT-230UC/21-21/EX - 2909516


Diagram



Interrupting rating

## Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

Circuit diagram



### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.0 | 27371600 |
| eCl@ss 5.1 | 27371600 |
| eCl@ss 6.0 | 27371600 |
| eCl@ss 7.0 | 27371601 |
| eCl@ss 8.0 | 27371601 |
| eCl@ss 9.0 | 27371601 |

ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC001437 |
| ETIM 3.0 | EC001437 |
| ETIM 4.0 | EC001437 |
| ETIM 5.0 | EC001437 |
| ETIM 6.0 | EC001437 |
| ETIM 7.0 | EC001437 |

UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211916 |
| UNSPSC 7.0901 | 39121515 |
| UNSPSC 11     | 39121515 |
| UNSPSC 12.01  | 39121515 |
| UNSPSC 13.2   | 39122334 |

## Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

### Classifications

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 18.0 | 39122334 |
| UNSPSC 19.0 | 39122334 |
| UNSPSC 20.0 | 39122334 |
| UNSPSC 21.0 | 39122334 |

### Approvals

#### Approvals

Approvals

DNV GL

Ex Approvals

IECEEx / ATEX / UL Listed / cUL Listed / EAC Ex / cULus Listed

#### Approval details

|        |                                                                                     |                                                                                   |               |
|--------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------------|
| DNV GL |  | <a href="https://approvalfinder.dnvgl.com/">https://approvalfinder.dnvgl.com/</a> | TAE0000196-02 |
|--------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------------|

### Accessories

#### Accessories

##### Bridge

Continuous plug-in bridge - FBST 500-PLC RD - 2966786



Continuous plug-in bridge, length: 500 mm, color: red

Continuous plug-in bridge - FBST 500-PLC BU - 2966692



Continuous plug-in bridge, length: 500 mm, color: blue



## Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

### Accessories

Continuous plug-in bridge - FBST 500-PLC GY - 2966838



Continuous plug-in bridge, length: 500 mm, color: gray

---

Single plug-in bridge - FBST 6-PLC RD - 2966236



Single plug-in bridge, length: 6 mm, number of positions: 2, color: red

---

Single plug-in bridge - FBST 6-PLC BU - 2966812



Single plug-in bridge, length: 6 mm, number of positions: 2, color: blue

---

Single plug-in bridge - FBST 6-PLC GY - 2966825



Single plug-in bridge, length: 6 mm, number of positions: 2, color: gray

---

Single plug-in bridge - FBST 8-PLC GY - 2967688



Single plug-in bridge, length: 8 mm, number of positions: 2, color: gray

---

## Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

### Accessories

Single plug-in bridge - FBST 14-PLC BK - 2967691



Single plug-in bridge, length: 14 mm, number of positions: 2, color: black

---

### DIN rail

DIN rail, unperforated - NS 35/ 7,5 V2A UNPERF 2000MM - 0801377



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Stainless steel V2A, uncoated, length: 2000 mm, color: silver

---

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733



DIN rail perforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

---

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM - 0801762



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Copper, uncoated, length: 2000 mm, color: copper-colored

---

DIN rail, unperforated - NS 35/15 UNPERF 2000MM - 1201714



DIN rail, unperforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

## Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

### Accessories

DIN rail, unperforated - NS 35/15 CU UNPERF 2000MM - 1201895



DIN rail, unperforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Copper, uncoated, length: 2000 mm, color: copper-colored

DIN rail, unperforated - NS 35/15-2,3 UNPERF 2000MM - 1201798



DIN rail, unperforated, Standard profile 2.3 mm, width: 35 mm, height: 15 mm, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756



DIN rail, unperforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Aluminum, uncoated, length: 2000 mm, color: silver

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730



DIN rail perforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

### Labeled terminal marker

## Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

### Accessories

Zack marker strip - ZB10,LGS:FORTL.ZAHLEN - 1053014



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snap into tall marker groove, for terminal block width: 10.2 mm, lettering field size: 10.15 x 10.5 mm, Number of individual labels: 10

---

### Partition plate

Separating plate - PLC-ATP BK - 2966841



Separating plate, 2 mm thick, required at the start and end of a PLC terminal strip. Furthermore, it is used for: visual separation of groups, safe isolation of different voltages of neighboring PLC relays in acc. with DIN VDE 0106-101, isolation

---

### Power module

Power terminal block - PLC-ESK GY - 2966508



Power terminal block, for the input of up to four potentials, for mounting on NS 35/7.5

---

### Screwdriver tools

Screwdriver - SZF 1-0,6X3,5 - 1204517



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

---

### Terminal marking

Zack marker strip - ZB10/WH-100:UNBEDRUCKT - 5060883



Zack marker strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snap into tall marker groove, for terminal block width: 10.2 mm, lettering field size: 10.15 x 10.5 mm, Number of individual labels: 1000

## Relay Module - PLC-RPT-230UC/21-21/EX - 2909516

### Accessories

Zack marker strip - ZB 10:UNBEDRUCKT - 1053001



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snap into tall marker groove, for terminal block width: 10.2 mm, lettering field size: 10.5 x 10.15 mm, Number of individual labels: 10

---

Marker for terminal blocks - UC-TM 12 - 0819194



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snap into tall marker groove, for terminal block width: 12 mm, lettering field size: 11.45 x 10.5 mm, Number of individual labels: 40

---

Marker for terminal blocks - UCT-TM 12 - 0829144



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snap into tall marker groove, for terminal block width: 12 mm, lettering field size: 10.8 x 9.6 mm, Number of individual labels: 30

---

### Spare parts

Single relay - REL-MR-110DC/21-21/EX - 2908824



Plug-in miniature power relay, RT III sealed with power contacts, 2 changeover contacts, input voltage: 110 V DC, in connection with the corresponding PLC base approved in accordance with ATEX/IECEx (zone 2) and Ex zone class I, div. 2.