

Test adapter - PAIS-4-P/P GY - 3032794

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Test adapter, For 4 mm test plugs, color: gray

Your advantages

- ✓ Reliable contacting of test plugs with a 4 mm diameter in the function shaft
- ✓ Test adapter for accommodating safety test plugs with a 4 mm diameter

RoHS

Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 055626 011134
GTIN	4055626011134
Weight per Piece (excluding packing)	2.480 g
Custom tariff number	85366990
Country of origin	Poland

Technical data

Dimensions

Height	53.3 mm
Length	6.5 mm
Width	6 mm

General

Note	Only use in UDK 4 MTK-P/P and UK 5-MTK-P/P
	Do not plug in while the power is connected
Color	gray
Material	Copper alloy
Ambient temperature (operation)	-40 °C ... 125 °C

Test adapter - PAIS-4-P/P GY - 3032794

Technical data

Max. voltage	250 V
Maximum load current	10 A

Standards and Regulations

Flammability rating according to UL 94	V0
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 4.0	27141127
eCl@ss 4.1	27141127
eCl@ss 5.0	27141127
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141148
eCl@ss 8.0	27141148
eCl@ss 9.0	27141148

ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC002255
ETIM 5.0	EC002555
ETIM 6.0	EC002555

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	20122006