

## Female test connector - PSBJ-URTK 6 VT - 3026421

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Female test connector, Color: violet

### Why buy this product

- ✓ The test socket PSBJ... is used in place of the normal bridge screw and ensures the voltage pick-off on a bridged group of terminals
- ✓ The test sockets are tailored to the special applications encountered in the power supply industry

RoHS

### Key Commercial Data

|                        |                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit           | 1 STK                                                                                                   |
| Minimum order quantity | 10 STK                                                                                                  |
| GTIN                   | <br>4 017918 351182 |
| GTIN                   | 4017918351182                                                                                           |
| Custom tariff number   | 85366990                                                                                                |
| Country of origin      | Poland                                                                                                  |

### Technical data

#### Dimensions

|              |        |
|--------------|--------|
| Length       | 6 mm   |
| Width        | 6 mm   |
| Pin diameter | 4.1 mm |

#### General

|          |        |
|----------|--------|
| Color    | violet |
| Material | Brass  |

## Female test connector - PSBJ-URTK 6 VT - 3026421

### Technical data

#### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141127 |
| eCl@ss 4.1 | 27141127 |
| eCl@ss 5.0 | 27141127 |
| eCl@ss 5.1 | 27141111 |
| eCl@ss 6.0 | 27141148 |
| eCl@ss 7.0 | 27141148 |
| eCl@ss 8.0 | 27440313 |
| eCl@ss 9.0 | 27440313 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000489 |
| ETIM 3.0 | EC000489 |
| ETIM 4.0 | EC002255 |
| ETIM 5.0 | EC002255 |
| ETIM 6.0 | EC002255 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211812 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121411 |
| UNSPSC 12.01  | 39121411 |
| UNSPSC 13.2   | 39121410 |

### Approvals

#### Approvals

---

Approvals

EAC / EAC

---

# Female test connector - PSBJ-URTK 6 VT - 3026421

## Approvals

Ex Approvals

---

### Approval details

|     |                                                                                   |                     |
|-----|-----------------------------------------------------------------------------------|---------------------|
| EAC |  | 7500651.22.01.00246 |
|-----|-----------------------------------------------------------------------------------|---------------------|

|     |                                                                                   |               |
|-----|-----------------------------------------------------------------------------------|---------------|
| EAC |  | EAC-Zulassung |
|-----|-----------------------------------------------------------------------------------|---------------|