

Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail power supply unit 24 V DC/30 A, primary switched-mode, 3-phase.



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	3859.8 GRM
Custom tariff number	85044030
Country of origin	Germany

Technical data

Dimensions

Width	240 mm
Height	130 mm
Depth	130 mm
Width with alternative assembly	122 mm
Height with alternative assembly	243 mm
Depth with alternative assembly	243 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 70 °C (> 60 °C derating)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	95 % (at 25 °C, non-condensing)
Noise immunity	EN 61000-6-2:2005

Input data

Nominal input voltage range	3x 400 V AC ... 500 V AC
-----------------------------	--------------------------

Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Technical data

Input data

Input voltage range	3x 320 V AC ... 575 V AC (for all three phases)
	450 V DC ... 800 V DC
AC frequency range	45 Hz ... 65 Hz
Frequency range DC	0 Hz
Current consumption	approx. 3x 2.1 A (400 V AC)
	3x 1.7 A (480 V AC)
Inrush surge current	< 15 A (typical)
Power failure bypass	> 20 ms (at 3 x 400 V AC)
	> 20 ms (at 3 x 480 V AC)
Input fuse	Externally via 3 circuit breakers 6 A, 10 A or 16 A, characteristic B

Output data

Nominal output voltage	24 V DC $\pm 1\%$
Setting range of the output voltage	22.5 V ... 28.5 V
Output current	30 A (up to 60°C)
	35 A (with POWER BOOST)
Connection in parallel	Yes, for assembling redundant systems and increasing efficiency
Residual ripple	< 100 mV _{PP}
Peak switching voltages nominal load	< 100 mV _{PP} (20 MHz)
Maximum power dissipation NO-Load	< 14 W
Power loss nominal load max.	< 62 W

General

Net weight	3.3 kg
Operating voltage display	Green LED
Efficiency	> 92 %
Insulation voltage input/output	2 kV (routine test)
	4 kV (type test)
Protection class	I (with PE connection)
MTBF (IEC 61709, SN 29500)	> 500000 h
Mounting position	On horizontal DIN rail NS 35 in acc. with EN 60715
Assembly instructions	Can be aligned: vertical with spacing = 5 cm
Electromagnetic compatibility	Conformance with EMC directive 89/336/EC
Noise emission	EN 50081-2
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV)
	EN 61558-2-17
Standard - Safe isolation	DIN VDE 0100-410
	DIN VDE 0106-1010

Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Technical data

Connection data, input

Connection method	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	6 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	4 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	10
Stripping length	8 mm
Screw thread	M3

Connection data, output

Connection method	Screw connection
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	16 mm ²
Conductor cross section stranded min.	0.5 mm ²
Conductor cross section stranded max.	10 mm ²
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	6
Stripping length	10 mm

Signaling

Output name	Active
Output description	$U_{OUT} > 0.9 \times U_N$: High signal
Output voltage	+ 24 V DC (Signal)
Continuous load current	max. 40 mA
Status display	Green LED ($U_{out} < 0.9 \times U_N$: LED flashes)
Output name	floating
Output description	Relay contact, $U_{OUT} > 0.9 \times U_N$: Contact closed
Maximum switching voltage	≤ 30 V AC/DC
Maximum inrush current	≤ 1 A
Continuous load current	≤ 1 A

Classifications

eCl@ss

eCl@ss 4.0	27040702
eCl@ss 4.1	27040702
eCl@ss 5.0	27049002

Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Classifications

eCl@ss

eCl@ss 5.1	27049002
eCl@ss 6.0	27049002
eCl@ss 7.0	27049002
eCl@ss 8.0	27049002

ETIM

ETIM 2.0	EC001039
ETIM 3.0	EC001039
ETIM 4.0	EC000599
ETIM 5.0	EC002540

UNSPSC

UNSPSC 6.01	30211502
UNSPSC 7.0901	39121004
UNSPSC 11	39121004
UNSPSC 12.01	39121004
UNSPSC 13.2	39121004

Approvals

Approvals

Approvals

UL Recognized / UL Listed / cUL Recognized / GOST / cUL Listed / GL / DNV / IECCEB Scheme / SEMI F47 / cUL Listed / cULus Recognized / cULus Listed / cULus Listed / null / null / null / null

Ex Approvals

UL Listed / cUL Listed / cUL Listed / cULus Listed / cULus Listed

Approvals submitted

Approval details

UL Recognized 

Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Approvals

UL Listed 

cUL Recognized 

GOST 

cUL Listed 

GL

DNV

IECEE CB Scheme 

SEMI F47

cUL Listed 

cULus Recognized 

cULus Listed 

Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Approvals

cULus Listed


cULus Listed



Accessories

Accessories

Assembly adapter


Assembly adapters - UWA 182/52 - 2938235




Universal wall adapter

Drawings

Dimensioned drawing




Block diagram




Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633


Diagram



Circuit diagram




Circuit diagram




max.
30 VAC/DC, 1A

Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Circuit diagram




Circuit diagram




Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Product drawing




Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Product drawing




Diagram




Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Schematic diagram




Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Schematic diagram




Circuit diagram




Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Connection diagram




Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Dimensioned drawing



Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Product drawing



Power supply unit - QUINT-PS-3X400-500AC/24DC/30 - 2938633

Schematic diagram

