

## Coupling relay - PSR-PC50-1NO-1DO-24DC-SP - 2904665

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling relay for SIL 3 low-demand applications, couples digital output signals to the I/O, 1 enabling current path, module for F&G applications, test pulse filter, width: 17.5 mm, pluggable Push-in terminal block

The figure shows a version with a screw connection

### Your advantages

- ✓ Up to SIL 3 according to IEC 61508
- ✓ Easy proof test according to IEC 61508 thanks to integrated signal contact
- ✓ Installation in zone 2 permitted
- ✓ Couples digital output signals from failsafe controllers to I/O devices (valves, etc.) for electrical isolation and power adaptation
- ✓ Time saving push-in connection, tools not required
- ✓ Potentials can be easily looped through – ideal for BUS applications
- ✓ Intuitive use through colour coded actuation lever
- ✓ Can be combined with the MSTB 2,5 range
- ✓ Quick and convenient testing using integrated test option



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 046356 919920 |
| GTIN                                 | 4046356919920                                                                                           |
| Weight per Piece (excluding packing) | 212.400 g                                                                                               |
| Custom tariff number                 | 85364900                                                                                                |
| Country of origin                    | Germany                                                                                                 |
| Note                                 | Made to Order (non-returnable)                                                                          |

### Technical data

Note

# Coupling relay - PSR-PC50-1NO-1DO-24DC-SP - 2904665

## Technical data

### Note

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---------------------------------------------------------------------------|

### Dimensions

|        |          |
|--------|----------|
| Width  | 17.5 mm  |
| Height | 117.4 mm |
| Depth  | 114.5 mm |

### Ambient conditions

|                                                |                                                     |
|------------------------------------------------|-----------------------------------------------------|
| Ambient temperature (operation)                | -20 °C ... 55 °C                                    |
| Ambient temperature (storage/transport)        | -40 °C ... 65 °C                                    |
| Max. permissible relative humidity (operation) | 75 % (on average, 85% infrequently, non-condensing) |
| Max. permissible humidity (storage/transport)  | 75 % (on average, 85% infrequently, non-condensing) |
| Maximum altitude                               | ≤ 2000 m (Above sea level)                          |

### Power supply

|                                            |                                                   |
|--------------------------------------------|---------------------------------------------------|
| Rated control circuit supply voltage $U_s$ | 24 V DC -15 % / +10 % (A1/A2)                     |
|                                            | 20.4 V DC ... 26.4 V DC                           |
| Rated control supply current $I_s$         | typ. 65 mA (A1/A2)                                |
| Inrush current                             | ≤ 200 mA (A1/A2)                                  |
| Filter time                                | < 2 ms (Test pulse duration)                      |
|                                            | ≥ 100 ms (Test pulse rate)                        |
| Diagnostic supply voltage $U_D$            | 24 V DC -15 % / +10 % (24V/A2)                    |
| Input current at $U_D$                     | typ. 15 mA (24V/A2; depending on load M1 +100 mA) |
| Inrush current at $U_D$                    | 2.5 A (24V/A2; for 10 μs)                         |
| Protective circuit                         | Overload protection Suppressor diode              |

### Digital inputs

|                     |                                  |
|---------------------|----------------------------------|
| Number of inputs    | 3 (Test point for proof test)    |
| Inrush current      | 200 mA (Inputs TP1, TP2 and TP3) |
| Current consumption | typ. 20 mA (Input TP1)           |
|                     | typ. 18 mA (Input TP2)           |
|                     | typ. 35 mA (Input TP3)           |

### Relay outputs: enabling current path

|                    |                                     |
|--------------------|-------------------------------------|
| Output name        | Enabling current path               |
| Output description | safety-related N/O contacts         |
| Number of outputs  | 1 (undelayed)                       |
| Contact type       | 1 enabling current path             |
| Contact material   | AgNi, gold-flashed                  |
| Switching voltage  | min. 15 V AC/DC without diagnostics |
|                    | min. 20 V AC/DC (with diagnostics)  |
|                    | max. 250 V AC                       |
|                    | max. 125 V DC                       |

# Coupling relay - PSR-PC50-1NO-1DO-24DC-SP - 2904665

## Technical data

### Relay outputs: enabling current path

|                                               |                                                                                       |
|-----------------------------------------------|---------------------------------------------------------------------------------------|
| Limiting continuous current                   | 5 A                                                                                   |
| Inrush current                                | min. 100 mA                                                                           |
|                                               | max. 5 A                                                                              |
| Switching capacity                            | min. 1.5 W                                                                            |
| Switching frequency                           | max. 0.5 Hz                                                                           |
| Diagnostic threshold                          | 20 $\Omega$ ... 18 k $\Omega$ (lower/upper)                                           |
| Max. permissible overall conductor resistance | < 10 $\Omega$ (LO/LO' and NI/NI' and load resistance in the event of a short circuit) |
| Mechanical service life                       | approx. $5 \times 10^7$ cycles                                                        |

### Alarm outputs

|                          |                    |
|--------------------------|--------------------|
| Output description       | non-safety-related |
| Number of outputs        | 1 (digital)        |
| Voltage                  | 23 V DC            |
| Current                  | max. 100 mA        |
| Short-circuit protection | no                 |
| Output fuse              | 150 mA fast blow   |

### Times

|                            |                                |
|----------------------------|--------------------------------|
| Typical pickup time at US  | 30 ms (when controlled via A1) |
| Typical release time at US | 30 ms (when controlled via A1) |
| Recovery time              | 1 s                            |

### General

|                                             |                                                                                   |
|---------------------------------------------|-----------------------------------------------------------------------------------|
| Relay type                                  | Electromechanical relay with forcibly guided contacts in accordance with EN 50205 |
| Nominal operating mode                      | 100% operating factor                                                             |
| Net weight                                  | 212.4 g                                                                           |
| Mounting position                           | vertical or horizontal                                                            |
| Mounting type                               | DIN rail mounting                                                                 |
| Degree of protection                        | IP20                                                                              |
| Min. degree of protection of inst. location | IP54                                                                              |
| Housing material                            | PBT                                                                               |
| Housing color                               | yellow                                                                            |
| Operating voltage display                   | Yellow LED                                                                        |
| Status display                              | Green LED                                                                         |
| Indication                                  | Red LED                                                                           |

### Connection capacity

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| Connection method                | Push-in spring connection                   |
| pluggable                        | Yes                                         |
| Conductor cross section solid    | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Conductor cross section flexible | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |

# Coupling relay - PSR-PC50-1NO-1DO-24DC-SP - 2904665

## Technical data

### Connection capacity

|                                                                       |                                                      |
|-----------------------------------------------------------------------|------------------------------------------------------|
| Conductor cross section AWG / kcmil                                   | 24 ... 16                                            |
| Conductor cross section flexible, with ferrule without plastic sleeve | 0.25 mm² ... 1.5 mm² (only together with CRIMPFOX 6) |
| Conductor cross section, flexible, with ferrule, with plastic sleeve  | 0.25 mm² ... 1.5 mm² (only together with CRIMPFOX 6) |
| Stripping length                                                      | 8 mm                                                 |

### Safety-related characteristic data

|                              |                        |
|------------------------------|------------------------|
| Designation                  | IEC 61508 - Low demand |
| Safety Integrity Level (SIL) | 3 (15 % of total SIL)  |

### Standards and Regulations

|                                |                                                                  |
|--------------------------------|------------------------------------------------------------------|
| Designation                    | Air clearances and creepage distances between the power circuits |
| Standards/regulations          | DIN EN 50178                                                     |
| Rated insulation voltage       | 250 V AC                                                         |
| Rated surge voltage/insulation | 6 kV/safe isolation (through protective impedance)               |
| Degree of pollution            | 2                                                                |
| Overvoltage category           | III                                                              |
| Shock                          | 15g                                                              |
| Vibration (operation)          | 2g                                                               |
| Conformance                    | CE-compliant                                                     |
| ATEX                           | # II 3 G Ex nA nC IIC T4 Gc                                      |
| IECEX                          | Ex nA nC IIC T4 Gc                                               |
| UL, USA/Canada                 | cULus                                                            |
|                                | Class I, Zone 2, AEx nA nC IIC T4 / Ex nA nC IIC Gc T4 X         |
|                                | Class I, Div. 2, Groups A, B, C, D, T4                           |
| GL                             | C, EMC2                                                          |
| Environmental simulation test  | ISA-S71.04 (G3)                                                  |


### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Drawings

Coupling relay - PSR-PC50-1NO-1DO-24DC-SP - 2904665

Block diagram



Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 40020600 |
| eCl@ss 4.1 | 40020600 |
| eCl@ss 5.0 | 27371900 |
| eCl@ss 5.1 | 27371900 |
| eCl@ss 6.0 | 27371800 |
| eCl@ss 7.0 | 27371819 |
| eCl@ss 8.0 | 27371819 |
| eCl@ss 9.0 | 27371819 |

ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC001449 |
| ETIM 5.0 | EC001449 |
| ETIM 6.0 | EC001449 |
| ETIM 7.0 | EC001449 |

Approvals

Approvals

Approvals

GL / UL Listed / cUL Listed / Functional Safety / EAC / cULus Listed

Ex Approvals

IECEX / ATEX / UL Listed / cUL Listed / cULus Listed

## Coupling relay - PSR-PC50-1NO-1DO-24DC-SP - 2904665

### Approvals

#### Approval details

|                   |                                                                                     |                                                                                                                                                       |                          |
|-------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| GL                |    | <a href="https://approvalfinder.dnvgl.com/">https://approvalfinder.dnvgl.com/</a>                                                                     | 11253-14 HH              |
| UL Listed         |    | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 140324            |
| cUL Listed        |    | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 140324            |
| Functional Safety |   |                                                                                                                                                       | 968/FSP 1011.00/14       |
| EAC               |  |                                                                                                                                                       | RU C-<br>DE.A*30.B.01082 |
| cULus Listed      |  |                                                                                                                                                       |                          |