

Option module - NLC-MOD-RTC - 2701153

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Real-time clock

Your advantages

- ✓ Optional on NLC-050... base units, standard on NLC-055... base units
- ✓ Allows time and date comparisons within a project
- ✓ Can be set via operator panel or nanoNavigator
- ✓ Supports month-day-year, day-month-year, and year-month-day formats

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 324663
GTIN	4046356324663
Weight per Piece (excluding packing)	34.800 g
Custom tariff number	91109000
Country of origin	India
Note	Made to Order (non-returnable)

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	24.5 mm
Height	25.5 mm
Depth	49 mm

Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
---------------------------------	------------------

Option module - NLC-MOD-RTC - 2701153

Technical data

Ambient conditions

Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	90 %

Interfaces

Interface	Realtime Clock
Connection method	Slot 2

Supply

Supply voltage	24 V DC (Power available via logic module)
Max. current consumption	10 mA
Typical current consumption	4 mA

Realtime clock

Realtime clock	Yes (battery-backed)
Accuracy realtime clock	2 s/day at 25 °C
	4.5 s/day overall (60°C)
Battery	Life 5 years

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 4.0	27250300
eCl@ss 4.1	27250300
eCl@ss 5.0	27242700
eCl@ss 5.1	27242700
eCl@ss 6.0	27242200
eCl@ss 7.0	27242216
eCl@ss 8.0	27242216
eCl@ss 9.0	27242216

ETIM

ETIM 2.0	EC001417
ETIM 3.0	EC001417
ETIM 4.0	EC001417
ETIM 5.0	EC001417
ETIM 6.0	EC001417
ETIM 7.0	EC001417

Option module - NLC-MOD-RTC - 2701153

Classifications

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	39122329
UNSPSC 18.0	39122329
UNSPSC 19.0	39122329
UNSPSC 20.0	39122329
UNSPSC 21.0	39122329

Approvals

Approvals

Approvals

UL Listed

Ex Approvals

Approval details

UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
-----------	---	---	---------------

Accessories

Accessories

Cover

Covering hood - NLC-MOD-CAP-PXC - 2701292



Replacement cover for slot 2 in base unit.