

# NLC-MOD-USB

Order No.: 2701195



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2701195>

Serial connection to PC's USB port for data transfer or software  
configuration

| Commercial data          |                                                                                                       |
|--------------------------|-------------------------------------------------------------------------------------------------------|
| EAN                      | <br>4 046356 325400 |
| sales group              | K254                                                                                                  |
| Pack                     | 1 Pcs.                                                                                                |
| Customs tariff           | 85366990                                                                                              |
| Gross weight in pieces   | 0.0411 KG                                                                                             |
| Net weight per piece     | 0.0398 KG                                                                                             |
| Catalog page information | Page 530 (C-8-2013)                                                                                   |

## Product notes

WEEE/RoHS-compliant since:  
04/17/2008



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Product description

Slot 1 option module. Connects the Nanoline controller to a Type A USB port. Functions as a serial device and requires special driver included on nanoNavigator CD.

## Technical data

| Dimensions |         |
|------------|---------|
| Width      | 24.5 mm |
| Height     | 25.5 mm |

|       |       |
|-------|-------|
| Depth | 49 mm |
|-------|-------|

#### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Degree of protection                    | IP20             |
| Ambient temperature (operation)         | -25 °C ... 60 °C |
| Ambient temperature (storage/transport) | -25 °C ... 85 °C |

#### Interfaces

|                     |            |
|---------------------|------------|
| Interface           | USB        |
| Connection method   | USB Type B |
| Transmission length | 2 m        |

#### Supply

|                             |                                            |
|-----------------------------|--------------------------------------------|
| Supply voltage              | 24 V DC (Power available via logic module) |
| Max. current consumption    | 18 mA                                      |
| Typical current consumption | 10 mA                                      |

#### Certificates / Approvals



Certification UL Listed

Certifications applied for:

Certification Ex:

#### Accessories

| Item           | Designation       | Description                                |
|----------------|-------------------|--------------------------------------------|
| <b>General</b> |                   |                                            |
| 2701289        | NLC-MOD-CAP       | Replacement cover for slot 1 in base unit. |
| 2701247        | NLC-PC/USB-CBL 2M | <b>Cable</b> , serial                      |

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact  
Technical modifications reserved;