

Program / configuration memory - SD FLASH 2GB PLCNEXT MEMORY - 1043501

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Program and configuration memory for storing the application programs and other files in the file system of the PLC, plug-in, 2 GB.

Your advantages

- ✓ Program and configuration memory
- ✓ For storing application programs and other files in the file system of the PLC



PLCnext Technology[®]
Designed by PHOENIX CONTACT

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 607573
GTIN	4055626607573
Weight per Piece (excluding packing)	8.500 g
Custom tariff number	85235190
Country of origin	Germany

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

General

Supply voltage	3.3 V DC
Supply voltage range	2.7 V DC ... 3.6 V DC

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Program / configuration memory - SD FLASH 2GB PLCNEXT MEMORY - 1043501

Classifications

eCI@ss

eCI@ss 5.0	24210100
eCI@ss 5.1	24210100
eCI@ss 6.0	19150700
eCI@ss 7.0	19150702
eCI@ss 8.0	27242212
eCI@ss 9.0	27242212

ETIM

ETIM 5.0	EC000192
ETIM 6.0	EC000192
ETIM 7.0	EC000192

Accessories

Accessories

Controller

Controller - AXC F 2152 - 2404267



PLCnext Control for the direct control of Axioline F I/Os. With two Ethernet interfaces. Complete with connector and bus base module.

Safety controller - RFC 4072S - 1051328



PLCnext Control with 4 x 10/100/1000 Ethernet, PROFINET controller with integrated PROFIsafe safety controller, PROFINET device, IP20 degree of protection, pluggable parameterization memory