

SKBI 64/G64

Order No.: 2263117

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2263117>

Plug-in card block, Nominal current: 4 A, Nom. voltage: 250 V,
Pitch: 5.08 mm, Number of positions: 64, Connection type: Screw
connection, Color: green

Commercial data

EAN	4017918053895
Pack	1 pcs.
Customs tariff	85369010
Weight/Piece	0.3798 KG
Catalog page information	Page 527 (CC-2009)

Product notes

WEEE/RoHS-compliant since:
06/28/2006



[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Technical data**Dimensions / positions**

Length	66 mm
Height	162 mm
Width	118 mm
Pitch	5.08 mm

Number of positions	64
Hole diameter	4.2 mm
Screw thread	M3
Tightening torque, min	0.5 Nm
Tightening torque max	0.6 Nm

Technical data

Connection in acc. with standard	EN-VDE
Nominal current I_N	4 A
Nominal voltage U_N	250 V (in acc. with DIN VDE 0110/Gr.B)
Stripping length	8 mm

Connection data


Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

Accessories


Item	Designation	Description
Assembly		
2263007	SF-SKBI 64	Snap foot, for horizontal or vertical mounting of the SKBI plug-in card blocks, on the NS 35/7.5 DIN rail

Drawings

Dimensioned drawing



Schematic diagram



Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact
Technical modifications reserved;