



Catalog Numbers, Ratings – aM (Optional Blown-Fuse Indicator)

	SIZE (mm x mm)	RATED In CURRENT (A)	RATED VOLTAGE	CATALOG NUMBER		INTERRUPTING RATING (A)	STANDARD PACK/CTN.	
				w/o Indicator	w/Indicator			
15519-G	8 x 31	1	400V	15511-G	-	20,000	10/100	
		2		15513-G	-			
		4		15519-G	-			
		6		15523-G	-			
		8		15527-G	-			
		10		15531-G	-			
16535-G	10 X 38	0.16	500V	16503-G	-	120,000	10/100	
		0.25		16507-G	-			
		0.5		16509-G	-			
		1		16511-G	16711-G			
		2		16513-G	16713-G			
		4		16519-G	16719-G			
		6		16523-G	16723-G			
		8		16527-G	16727-G			
		10		16531-G	16731-G			
		12		16533-G	16733-G			
		16		16535-G	16735-G			
		20		16537-G	16737-G			
		25	400V	16539-G	16739-G			
		32		16543-G				
17535-G	14 X 51	0.25	690V	17507-G	-	80,000	10/50	
		0.5		17509-G	-			
		1		17511-G	17711-G			
		2		17513-G	17713-G			
		4		17519-G	17719-G			
		6		17523-G	17723-G			
		8		17527-G	17727-G			
		10		17531-G	17731-G			
		12		17533-G	17733-G			
		16		17535-G	17735-G			
		20		17537-G	17737-G			
		25		17539-G	17739-G			
		32	500V	17543-G	17743-G	120,000		
		40		17547-G	17747-G			
		45		17549-G	17749-G			
		50	400V	17551-G	17751-G			
18555-G	22 x 58	4	690V	18519-G	18719-G	80,000	10/50	
		6		18523-G	18723-G			
		8		18527-G	18727-G			
		10		18531-G	18731-G			
		12		18533-G	18733-G			
		16		18535-G	18735-G			
		20		18537-G	18737-G			
		25		18539-G	18739-G			
		32		18543-G	18743-G			
		40		18547-G	18747-G			
		50		18551-G	18751-G			
		63		18555-G	18755-G			
		80		18559-G	18759-G			
		100	500V	18563-G	18763-G	120,000		
		125		400V	18565-G			18765-G

Blown-Fuse Indicator



Dimensions

FUSE SIZE	A	B	C
8 x 31	8.5	31.5	6.3
10 x 38	10.3	38	10.5
14 x 51	14.3	51	13.8
22 x 58	22.2	58	16.2