

SHALL NOT BE REPRODUCED, DISTRIBUTED, OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.

REEL DIA. REF.

FEED DIRECTION

Ø.500 [12.7] MAX. HOLE THRU

±.005 [±0.13] Ø.059 [Ø1.50] DIA. HOLE

±.005 [±0.13]

.945 [24.00]

.161 [4.09]

.079 [2.0]

.210 [5.33] REF.

±.005 [±0.13]

1.732 [44.0]

FEED DIRECTION

.016 [0.4] REF.

1. TAPE:  
MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER  
ANSI/EIA-481 STANDARD

2. REEL:  
13.0 [330.2] DIA. 500 PIECES OF  
PART NO. 2896 PER REEL.

|                                                                                                           |                    |                            |                          |
|-----------------------------------------------------------------------------------------------------------|--------------------|----------------------------|--------------------------|
| <h1>KEYSTONE ELECTRONICS CORP.</h1> <p>www.keyelco.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500</p> |                    |                            |                          |
| PART NAME<br><h2>SM COIN CELL CLIP ON TAPE</h2>                                                           |                    |                            |                          |
| MATERIAL<br><h2>AS NOTED</h2>                                                                             |                    |                            |                          |
| FINISH<br><h2>AS NOTED</h2>                                                                               |                    | DRN BY<br><h2>NT</h2>      | DATE<br><h2>9.19.18</h2> |
|                                                                                                           |                    | APP'D<br><h2>LN</h2>       | SCALE<br><h2>X</h2>      |
| TOLERANCES<br>DECIMAL $\pm .015$ [ $\pm 0.38$ ]<br>ANGULAR $\pm 1^\circ$<br>UNLESS OTHERWISE SPECIFIED    | CODE<br><h2>C</h2> | DWG NO.<br><h1>2896TR</h1> |                          |