

THIS DOCUMENT IS THE PROPERTY OF
KEYSTONE ELECTRONICS CORP. AND
SHALL NOT BE REPRODUCED, DISTRIBUTED
OR USED AS A BASIS FOR MANUFACTURE
WITHOUT PRIOR WRITTEN PERMISSION
FROM KEYSTONE ELECTRONICS CORP.

REEL DIA. REF.

FEED DIRECTION

Ø.500 [12.7] MAX. HOLE THRU

±.005 [±0.13]

Ø.059 [Ø1.50] DIA. HOLE

±.005 [±0.13]

1.732 [44.0]

±.005 [±0.13]

.945 [24.00]

±.005 [±0.13]

.161 [4.09]

.079 [2.0]

.210 [5.33] REF.

FEED DIRECTION

.016 [0.4] REF.

NOTES:

TAPE AND REEL SPECIFICATIONS:

1. TAPE:

MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANSI/EIA-481 STANDARD

2. REEL:

13.0 [330.2] DIA. 500 PIECES OF
PART NO. 2898 PER REEL.

KEYSTONE ELECTRONICS CORP.

www.keyelco.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500

PART NAME

SM COIN CELL CLIP ON TAPE

MATERIAL

AS NOTED

FINISH

AS NOTED

DRN BY

NT

DATE

9.19.18

APP'D

LN

SCALE

X

TOLERANCES

INCH

[MM]

DECIMAL

±.015 [±0.38]

ANGULAR

± 1°

UNLESS OTHERWISE SPECIFIED

CODE

C

DWG NO.

2898TR

DATE

DESCRIPTION

REV.

TAPE AND REEL SPECIFICATIONS:

1. TAPE:
MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANSI/EIA-481 STANDARD

2. REEL:
13.0 [330.2] DIA. 500 PIECES OF
PART NO. 2898 PER REEL.

KEYSTONE ELECTRONICS CORP. www.keyelco.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500			
PART NAME SM COIN CELL CLIP ON TAPE			
MATERIAL AS NOTED			
FINISH AS NOTED		DRN BY NT	DATE 9.19.18
		APP'D LN	SCALE X
TOLERANCES DECIMAL $\pm .015$ [MM] $[\pm 0.38]$ ANGULAR $\pm 1^\circ$ UNLESS OTHERWISE SPECIFIED	CODE C	DWG NO. 2898TR	