

WE-LHMI

SMD Low Profile High Current Molded Inductor



4020	744 373 240 010	
	L:	0.10 μ H
	I _R :	12.0 A
	I _{sat} :	30.0 A
	R _{DC typ} :	3.2 m Ω

4020	744 373 240 022	
	L:	0.22 μ H
	I _R :	9.5 A
	I _{sat} :	17.0 A
	R _{DC typ} :	6.6 m Ω

4020	744 373 240 033	
	L:	0.33 μ H
	I _R :	8.0 A
	I _{sat} :	16.5 A
	R _{DC typ} :	7.8 m Ω

4020	744 373 240 047	
	L:	0.47 μ H
	I _R :	6.8 A
	I _{sat} :	14.5 A
	R _{DC typ} :	11.2 m Ω

4020	744 373 240 056	
	L:	0.56 μ H
	I _R :	6.0 A
	I _{sat} :	10.5 A
	R _{DC typ} :	13.5 m Ω

4020	744 373 240 068	
	L:	0.68 μ H
	I _R :	5.5 A
	I _{sat} :	10.0 A
	R _{DC typ} :	16.0 m Ω

4020	744 373 240 10	
	L:	1.0 μ H
	I _R :	5.0 A
	I _{sat} :	9.0 A
	R _{DC typ} :	22.0 m Ω

4020	744 373 240 12	
	L:	1.20 μ H
	I _R :	4.7 A
	I _{sat} :	8.5 A
	R _{DC typ} :	25.0 m Ω

4020	744 373 240 15	
	L:	1.50 μ H
	I _R :	3.8 A
	I _{sat} :	8.0 A
	R _{DC typ} :	34.8 m Ω

4020	744 373 240 22	
	L:	2.20 μ H
	I _R :	3.25 A
	I _{sat} :	6.5 A
	R _{DC typ} :	51.0 m Ω

4020	744 373 240 33	
	L:	3.30 μ H
	I _R :	2.5 A
	I _{sat} :	4.2 A
	R _{DC typ} :	69.0 m Ω

4020	744 373 240 47	
	L:	4.70 μ H
	I _R :	2.2 A
	I _{sat} :	4.0 A
	R _{DC typ} :	95.0 m Ω

4020	744 373 240 56	
	L:	5.60 μ H
	I _R :	2.0 A
	I _{sat} :	3.8 A
	R _{DC typ} :	120 m Ω

4020	744 373 240 68	
	L:	6.80 μ H
	I _R :	1.75 A
	I _{sat} :	3.5 A
	R _{DC typ} :	150 m Ω

4020	744 373 240 82	
	L:	8.20 μ H
	I _R :	1.6 A
	I _{sat} :	2.8 A
	R _{DC typ} :	158 m Ω

4020	744 373 241 00	
	L:	10.0 μ H
	I _R :	1.5 A
	I _{sat} :	2.4 A
	R _{DC typ} :	215 m Ω

4020	744 373 241 50	
	L:	15.0 μ H
	I _R :	1.2 A
	I _{sat} :	2.1 A
	R _{DC typ} :	325 m Ω

4020	744 373 242 20	
	L:	22.0 μ H
	I _R :	1.0 A
	I _{sat} :	2.0 A
	R _{DC typ} :	470 m Ω

4012	744 373 210 010	
	L:	0.10 μ H
	I _R :	8.1 A
	I _{sat} :	24.0 A
	R _{DC typ} :	4.3 m Ω

4012	744 373 210 022	
	L:	0.22 μ H
	I _R :	7.7 A
	I _{sat} :	17.0 A
	R _{DC typ} :	6.6 m Ω

4012	744 373 210 047	
	L:	0.47 μ H
	I _R :	5.9 A
	I _{sat} :	9.0 A
	R _{DC typ} :	18.0 m Ω

4012	744 373 210 10	
	L:	1.0 μ H
	I _R :	4.0 A
	I _{sat} :	7.5 A
	R _{DC typ} :	41.0 m Ω

4012	744 373 210 15	
	L:	1.5 μ H
	I _R :	3.0 A
	I _{sat} :	4.4 A
	R _{DC typ} :	55.0 m Ω

4012	744 373 210 22	
	L:	2.2 μ H
	I _R :	2.5 A
	I _{sat} :	4.2 A
	R _{DC typ} :	69.2 m Ω

4012	744 373 210 33	
	L:	3.3 μ H
	I _R :	2.3 A
	I _{sat} :	3.9 A
	R _{DC typ} :	84.0 m Ω

4012	744 373 210 47	
	L:	4.7 μ H
	I _R :	1.9 A
	I _{sat} :	3.1 A
	R _{DC typ} :	128 m Ω

4012	744 373 210 56	
	L:	5.6 μ H
	I _R :	1.7 A
	I _{sat} :	2.7 A
	R _{DC typ} :	180 m Ω

4012	744 373 210 68	
	L:	6.8 μ H
	I _R :	1.4 A
	I _{sat} :	2.65 A
	R _{DC typ} :	300 m Ω

4012	744 373 210 82	
	L:	8.2 μ H
	I _R :	1.3 A
	I _{sat} :	2.4 A
	R _{DC typ} :	313 m Ω

4012	744 373 211 00	
	L:	10.0 μ H
	I _R :	1.2 A
	I _{sat} :	2.2 A
	R _{DC typ} :	410 m Ω

EMC COMPONENTS | **INDUCTORS** | TRANSFORMERS | RF COMPONENTS | CIRCUIT PROTECTION | EMC SHIELDING MATERIAL | LEDs | CONNECTORS | SWITCHES | ASSEMBLY TECHNIQUE | POWER ELEMENTS

Important information: Würth Elektronik's design kits contain reference components. These components correspond with the current product development status on the day of supply. Exchange of the reference components to components with up-to-date product development status is not carried out automatically. No liability is taken for the use of these reference components. Therefore, please request new samples prior to releases for series production and product release.

Please check datasheets on www.we-online.com for specifications. Würth Elektronik eiSos GmbH & Co. KG, EMC & Inductive Solutions. © 2014

www.we-online.com

All products
in stock!