

12VDC 4A Power Supply



Description:

This 12VDC 4A power supply has a 90-264vac input & a standard 2 pin Fig.8 input connector. It carries international safety approvals and meets latest energy efficiency requirement. Featuring high reliability with a M.T.B.F of 50K hours at 25 degrees C, the units provides a single voltage regulated output at 42W max, & is fitted with a 2.1 x 5.5 x 12mm conn. Polarity + ve centre

General Spec



Part Numbers	SW3126B		
Output	12vdc regulated (4A max)	Leakage Current	shall not exceed mA
Current Min.	0.01A	Input Current (RMS Max.)	max
Power (watts)	48W Max	Hi-Pot Spec	3000Vac 10mA 1 min. (I.P. to O.P.)
Line Reg	+/-5% at rated load	No load power consumption	Max
Total Output Regulation	+/-5 % at 0—100% load	Operating Temperature	0 to 40 degrees C
Ripple & Noise (mV p-p)	120mV P-P	Storage Temperature	-20 to 80 degrees C
Protections	Over Current and Short Circuit	Operating Humidity	10% to 90%
Case Size	126.4 x 52 x 35.5mm	Safety Approvals	CE, TUV, C-Tick, cUL, UL
Weight (approx.)	224g	EMC Standards	EN55022:2006+A1:2007 / EN6100-3-2 / EN6100-3-3
DC Cord	1.5 Metres	Pb-free	Yes RoHS Compliant
DC Plug	2.1 x 5.5 x 12mm +ve centre	MTBF	50K Hours at 25 degrees C
Rated Input Voltage	100-240Vac		
Full Input Voltage Range	90-264Vac		
Rated Frequency	50-60Hz		
Full Frequency Range	47-63Hz		
Efficiency	VI		

Full specification documents on each part included in this data sheet are available on request from PowerPax UK Ltd. PowerPax accepts no responsibility for typographical errors in the production of this leaflet. Product specifications are subject to change without notice