

NPN Silicon Planar Power Transistor

100V_{CB0}, 15A I_c, TO-3

multicompPRO

**RoHS
Compliant**



Applications

General Purpose Switching and Amplifier applications

Absolute Maximum Ratings (T_A = 25 °C)

Description	Symbol	Value	Units
Collector Base Voltage	V _{CB0}	100	V
Collector Emitter Voltage	V _{CEO}	60	
Collector Emitter Voltage(R _{BE} =100Ω)	V _{CER}	70	
Emitter Base Voltage	V _{EBO}	7	
Collector Current Continuous	I _c	15	A
Base Current	I _B	7	
Power Dissipation @ T _c =25°C Derate Above 25°C	P _{TOT}	115 0.657	W W/°C
Operating and Storage Junction Temperature Range	T _J , T _{STG}	- 65 to +200	°C

Thermal Characteristics

Characteristics	Symbol	Value	Unit
Junction-to-Case	R _{th(j-c)}	1.52	°C/W

Electrical Characteristics (T_C=25°C unless specified otherwise)

Description	Symbol	Test Condition	Min.	Max.	Units
Collector Emitter Sustaining Voltage	V _{CEO(sus)} *	I _c =200mA, I _B =0	60	-	V
Collector Emitter Sustaining Voltage	V _{CER(sus)} *	I _c =200mA, R _{BE} =100Ω	70	-	
Collector Cut off Current	I _{CEx}	V _{CE} =100V, V _{BE} =(off)=1.5V T _c =150°C V _{CE} =100V, V _{BE} =(off)=1.5V	-	1 5	mA
Collector Cut off Current	I _{CEO}	V _{CE} =30V, I _B =0	-	0.7	
Emitter Cut off Current	I _{EBO}	V _{BE} =7V, I _c =0	-	5	
Collector Emitter Saturation Voltage	V _{CE(Sat)} *	I _c =4A, I _B =400mA I _c =10A, I _B =3.3A	-	1.1 3	V
Base Emitter on Voltage	V _{BE(on)} *	I _c =4A, V _{CE} =4V	-	1.5	
DC Current Gain	h _{FE} *	I _c =4A, V _{CE} =4V I _c =10A, V _{CE} =4V	20 5	80	-

*Pulse Test: Pulse Width ≤300μs, Duty Cycle ≤2%

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicompPRO

NPN Silicon Planar Power Transistor

100V_{CBO}, 15A I_C, TO-3

multicompPRO


Second Breakdown

Description	Symbol	Test Condition	Min.	Max.	Units
Second Breakdown Collector Current with Base Forward Biased	I _{S/b}	V _{CE} =40V, t=1s, Nonrepetitive	2.87	-	A

Dynamic Characteristics

Description	Symbol	Test Condition	Min.	Max.	Units
Current Gain - Bandwidth Product	f _T	I _C =0.5A, V _{CE} =10V, f=1MHz	2.5	-	MHz
Small Signal Current Gain	h _{FE}	I _C =1A, V _{CE} =4V, f=1kHz	15	120	-
Small Signal Current Gain Cutoff Frequency	f _{HFE}	I _C =1A, V _{CE} =4V, f=1kHz	10	-	kHz

Typical Characteristics Curves



Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro



multicompPRO

NPN Silicon Planar Power Transistor
100V_{CBO}, 15A I_C, TO-3




Diagram

TO-3 Metal Can Package



Dim.	Min.	Max.
A	—	39.37
B	—	22.22
C	6.35	8.5
D	0.96	1.09
E	—	1.77
F	29.9	30.4
G	10.69	11.18
H	5.2	5.72
J	16.64	17.15
K	11.15	12.25
L	—	26.67
M	3.84	4.19



Pin Configuration
1. Base
2. Emitter
3. Collector

Part Number Table

Description	Part Number
NPN Silicon Planar Power Transistor, 15A, 100V, 115W	2N3055

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

