

Sentry SSR42 24VDC



Products → Low Voltage Products and Systems → Control Products → Electronic Relays and Controls
→ Safety Relays

Products → Low Voltage Products and Systems → Control Products → Safety Products → Safety Relays

General Information

Extended Product Type:	Sentry SSR42 24VDC
Product ID:	2TLA010053R0400
EAN:	7350024483338
Catalog Description:	Safety relay Sentry SSR42 24VDC - 24 volt DC - 2 NO + 2 NO (delayed) - OFF-Delay - 1.5 seconds
Long Description:	SSR42 is a safety relay with relay outputs, 2 NO + 2 delayed NO, and a +24 VDC supply voltage. SSR42 is used with safety devices with contacts, 1 or 2 channels, and safety devices with OSSD outputs. The reset function, automatic or manual, is set with a switch on the front. The two delayed NO relay outputs have an OFF-delay time of 1,5 seconds.

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364110

Popular Downloads

Data Sheet, Technical Information:	2TLC010001L0201
Instructions and Manuals:	2TLC010002M0201
Dimension Diagram:	2TLC010001U0201
Wiring Diagram:	2TLC010018T0001

Dimensions

Product Net Depth / Length:	120 mm
Product Net Height:	120 mm
Product Net Width:	22.5 mm
Product Net Weight:	0.207 kg

Technical

Performance Level (PL):	Up to e
Supply Voltage:	24 V DC

Certificates and Declarations (Document Number)

cUL Certificate:	2TLC010006D0201
Declaration of Conformity - CE:	2TLC010010D0201

Instructions and Manuals:	2TLC010002M0201
TÜV Certificate:	2TLC010009D0201

Classifications

Object Classification Code:	K
ETIM 4:	EC001449 - Device for monitoring of safety-related circuits
ETIM 5:	EC001449 - Device for monitoring of safety-related circuits
ETIM 6:	EC001449 - Device for monitoring of safety-related circuits
ETIM 7:	EC001449 - Device for monitoring of safety-related circuits
E-number:	3860824

