# TeSys VARIO - additional pole - 20 A - for V01





#### Main

Range	TeSys
Device short name	VZ
Product or component type	Additional pole
Performance level	High performance
Poles description	1P
Contacts type and composition	1 NO
Product compatibility	V01
Range compatibility	TeSys VARIO switch disconnector
Network type	DC AC
Network frequency	50/60 Hz
Suitability for isolation	Yes
· · · · · · · · · · · · · · · · · · ·	

#### Complementary

Left
690 V AC 50/60 Hz
8 kV
20 A
16 A
100000 cycles
100000 Cycles AC-21 30000 cycles DC-15
Power circuit screw clamp terminals 0.01 in² (6 mm²) flexible - with cable end Power circuit screw clamp terminals 0.02 in² (10 mm²) solid
Power circuit 18.59 lbf.in (2.1 N.m) screw clamp terminals
2.91 in (74 mm)
0.63 in (16 mm)
1.38 in (35 mm)
0.11 lb(US) (0.05 kg)

#### Environment

Standards	IEC 60947-3	
Product certifications	GL CSA UL	
Protective treatment	TC	
IP degree of protection	IP20 conforming to IEC 60529	
Mechanical robustness	Vibrations 10150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 30 Gn) IEC 60068-2-27	
Ambient air temperature for operation	-4122 °F (-2050 °C)	
Fire resistance	1760 °F (960 °C) IEC 60695-2-1	

## Ordering and shipping details

Category	21730 - V VARIO SWITCH	
Discount Schedule	CP1	
GTIN	00785901295846	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.1 lb(US) (0.05 kg)	
Returnability	No	
Country of origin	CZ	

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.46 in (3.7 cm)
Package 1 width	2.17 in (5.5 cm)
Package 1 Length	3.54 in (9 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	69
Package 2 Weight	8.07 lb(US) (3.659 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant    ☐EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes
Halogen content performance	Halogen free product

### Contractual warranty

Contraction Warranty		
Warranty	18 months	