


5mm Pitch Standard Profile 90° Rising Clamp Terminal

Features

- 2 & 3 pole double interlocking mechanism for increased strength
- 4-12 pole solid block end stackable
- Moulded in green UL94-V0 flame retardant PA66
- Professional rising clamp terminals
- 2.5mm² cable entry
- cUL, UL, CE approved
- Guided pin alignment
- Captive screws



CTB0150

Type No.	Poles	Length
CTB0150/2	2	10mm
CTB0150/3	3	15mm
CTB0150/4	4	20mm
CTB0150/5	5	25mm
CTB0150/6	6	30mm
CTB0150/7	7	35mm
CTB0150/8	8	40mm
CTB0150/9	9	45mm
CTB0150/10	10	50mm
CTB0150/11	11	55mm
CTB0150/12	12	60mm


Specification

Rating	20A/250V, UL=14A, CUL=14A, IMQ=24A, VDE=24A
Dielectric strength	≥2.5kV/60secs
Insulation resistance	≥5MΩ
Working temperature	-20°C to 125°C
Short period	160°C
Moulding	UL94-V0 flame retardant PA66
Pin/terminal	5μ tinned, nickel plated brass
Wire clamp	Nickel plated brass
Screw/torque	M3 steel, 6μ zinc colour passivated and tropicalised/0.5Nm

Recommended

PCB hole size ø1.3mm

CTB0150



For other dimensions see CTB0100