



### Electrical Test:

1. 100% Test(Open ,short ,miss wire)
2. Contact Resistance: 2 ohm max.
3. Insulation Resistance: 5M ohm min.
4. Hi-pot: 300V DC/10ms

### Pin Assignment

P1		P2	
(B4,B9,A4,A9)	VBus	VBus	Red
(A5)	CC	CC	Yellow
(A7)	D-	D-	White
(A6)	D+	D+	Green
(A1,A12,B1,B12)	GND	GND	Drain
	Shell	Shell	Shield

NO	DESCRIPTION	Q'TY	UNIT	TOLERANCE			TITLE:	DRAWING NO.:	REV.
				INCHES	M/M				
6	Metal DOWN Cap	1	pcs	.X	.015	.30	USB2.0 Type Cable C TO C White L=2M	CPC	A01
5	Metal UP Cap	1	pcs	.XX	.010	.10			
4	45P Color:White PVC	12	g	.XXX	.005	.05			
3	Inside Molding:Polyamide Resin	1	g	DRAWN BY 邱建联			CUSTOMER : PSG91491		C06026-00274
2	TYPEC-USB2.0 C Type Connector With PCB,Insulation:White,Shell Nickel Plated	2	pcs	CHECK BY			SCALE NONE	1/2	
1	NO UL 30AWG(19/0.06TC)*1P+22#(41/0.10TC+250D)*1C+30AWG(7/0.10TC)*1C+3E(26/0.10+250D)+AB(16/9/0.06TC 85%) OD:3.6 PVC White No Marking	AR	m	APPD BY			UNIT MM		2017.05.02
				DATE			2017.05.02		