

PRODUCT-DETAILS

DB16

DB16 Single Mounting Kit



General Information

Extended Product Type	DB16
Product ID	1SAZ701901R0001
EAN	4013614407819
Catalog Description	DB16 Single Mounting Kit
Long Description	DB16 Single Mounting Kit for T16

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Popular Downloads

Data Sheet, Technical Information	1SBC100173C0201
Instructions and Manuals	2CDC106024M6802
Dimension Diagram	1SAZ700411F0001

Dimensions

Product Net Width	92 mm
Product Net Height	50 mm

Product Net Depth / Length	73 mm
Product Net Weight	0.032 kg

Technical

Rated Operational Voltage	Main Circuit 690 V AC
Rated Operational Current (I _e)	16 A
Rated Operational Current AC-3 (I _e)	16 A
Rated Frequency (f)	Main Circuit 50 Hz Main Circuit 60 Hz
Rated Impulse Withstand Voltage (U _{imp})	Auxiliary Circuit 6 kV Main Circuit 6 kV
Rated Insulation Voltage (U _i)	690 V
Number of Poles	3
Degree of Protection	IP20
Pollution Degree	3
Connecting Capacity Main Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible 1x 0.75 ... 2.5 mm ² Rigid 1x 0.75 ... 4 mm ²
Tightening Torque	Main Circuit 1.1 ... 1.5 N·m
Wire Stripping Length	Main Circuit 12 mm
Recommended Screw Driver	Pozidriv 2
Mounting Position	Position 1 to 5
Suitable For	T16
Standards	CSA 22.2 No. 14 IEC/EN 60947-1 IEC/EN 60947-4-1 UL 508

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Ampere Rating UL/CSA	16 A
Connecting Capacity Main Circuit UL/CSA	Flexible 1x 18-10 AWG Stranded 1x 18-10 AWG
Tightening Torque UL/CSA	Main Circuit 13 in·lb

Environmental

Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 25g
Resistance to Vibrations acc. to IEC 60068-2-6	3g / 3 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

ABS Certificate	No Certificate Needed
cUL Certificate	cUL_E48139
Declaration of	1SAD938510-0182

Conformity - CE		
DNV Certificate		No Certificate Needed
GL Certificate		No Certificate Needed
GOST Certificate		1SAA941000-2704
Instructions and Manuals		2CDC106024M6802
LR Certificate		No Certificate Needed
RINA Certificate		No Certificate Needed
RMRS Certificate		No Certificate Needed
RoHS Information		1SAD938507-0182
UL Certificate		UL_E48139

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	92 mm
Package Level 1 Height	50 mm
Package Level 1 Depth / Length	73 mm
Package Level 1 Gross Weight	0.053 kg
Package Level 1 EAN	4013614407819
Package Level 2 Units	130 piece
Package Level 2 Width	215 mm
Package Level 2 Height	140 mm
Package Level 2 Depth / Length	200 mm
Package Level 2 Gross Weight	41.6 kg
Package Level 2 EAN	4013614480027

Classifications

ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC002498 - Accessories for low-voltage switch technology
ETIM 7	EC002498 - Accessories for low-voltage switch technology
eClass	7.0 27379201

Where Used (as part of "kit")

Identifier	Description	Type
3BHB047970R0008		Kit
3BHB047970R0009		Kit

Categories

Low Voltage Products and Systems → Control Products → Contactors → Thermal Overload Relays Accessories
Drives → Services → Spares and Consumables → Parts

