



circuit breaker 3VA2 IEC Frame 100 breaking capacity class L Icu=150 kA @ 415 V 4-pole, line protection ETU560, LSIG, In=40 A overload protection Ir=16 A...40 A short-circuit protection I_{sd}=0.6..10x I_n, I_i=1.5..12x I_n neutral conductor protection adjustable (OFF, up to 160%) ground-fault protection, can be switched off I_g=0.4...1 x I_n= tg=0.05-0.8s nut keeper kit

| Model | |
|---|---|
| product brand name | SENTRON |
| product designation | Molded case circuit breaker |
| design of the product | Line protection |
| design of the overcurrent release | ETU560 |
| protection function of the overcurrent release | LSIG |
| number of poles | 4 |
| General technical data | |
| insulation voltage / rated value | 800 V |
| operating voltage / at AC / rated value | 690 V |
| power loss [W] / maximum | 1.2 W |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 0.4 W |
| mechanical service life (operating cycles) / typical | 25 000 |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V | 15 000 |
| electrical endurance (operating cycles) / at AC-1 / at 690 V | 10 500 |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof | No |
| ground-fault monitoring version | Summation current formation L + N conductor |
| product function | |
| • communication function | Yes |
| • other measurement function | No |
| Net Weight | 3.2 kg |
| Current | |
| operational current | |
| • at 40 °C | 40 A |
| • at 45 °C | 40 A |
| • at 50 °C | 40 A |
| • at 55 °C | 40 A |
| • at 60 °C | 40 A |
| • at 65 °C | 40 A |
| • at 70 °C | 40 A |
| Switching capacity according to IEC 60947 | |
| switching capacity class of the circuit breaker | L |
| maximum short-circuit current breaking capacity (I _{cu}) | |
| • at 240 V | 200 kA |
| • at 415 V | 150 kA |
| • at 440 V | 150 kA |
| • at 500 V | 100 kA |
| • at 690 V | 25 kA |
| operating short-circuit current breaking capacity (I _{cs}) | |
| • at 240 V | 200 kA |
| • at 415 V | 150 kA |
| • at 440 V | 150 kA |
| • at 500 V | 100 kA |
| • at 690 V | 18 kA |
| short-circuit current making capacity (I _{cm}) | |
| • at 240 V | 440 kA |

- at 415 V
- at 440 V
- at 500 V
- at 690 V

330 kA
330 kA
220 kA
52.5 kA

Adjustable parameters

| | |
|--|-----------------------------|
| product feature / for L-tripping / can be switched on/off | No |
| adjustable response value setting current (I_r) / of the L-trip / with I2t characteristic | |
| • minimum | 16 A |
| • maximum | 40 A |
| adjustable response value delay time (t_r) / for L-tripping / with I2t characteristic | |
| • minimum | 0.5 s |
| • maximum | 25 s |
| adjustable response value setting current (I_{sd}) / of S-trip / with I0t characteristic | |
| • minimum | 24 A |
| • maximum | 400 A |
| adjustable response value setting current (I_{sd}) / of S-trip / with I2t characteristic | |
| • minimum | 24 A |
| • maximum | 400 A |
| adjustable response value delay time (t_{sd}) / for S-tripping / with I0t characteristic | |
| • minimum | 0.05 s |
| • maximum | 0.5 s |
| adjustable response value delay time (t_{sd}) / for S-tripping / with I2t characteristic | |
| • minimum | 0.05 s |
| • maximum | 0.5 s |
| adjustable response value setting current (I_l) / for I-tripping | |
| • minimum | 60 A |
| • maximum | 480 A |
| adjustable current response value current / for G-tripping / with standard characteristic | |
| • initial value | 16 A |
| • full-scale value | 40 A |
| adjustable response value delay time (t_g) / for G-tripping / with I0t characteristic | |
| • minimum | 0.05 s |
| • maximum | 0.8 s |
| adjustable response value setting current (I_g) / for G-tripping / with I2t characteristic | |
| • minimum | 16 A |
| • maximum | 40 A |
| adjustable response value delay time (t_g) / for G-tripping / with I2t characteristic | |
| • minimum | 0.05 s |
| • maximum | 0.8 s |
| adjustable setting current (I_{nN}) / for N-tripping | |
| • minimum | 16 A |
| • maximum | 64 A |
| design of the N-conductor protection | adjustable OFF; 40% to 160% |
| product function / grounding protection | Yes |

Mechanical Design

| | |
|------------------------|---------|
| product component | |
| • undervoltage release | No |
| • voltage trigger | No |
| • trip indicator | No |
| height [in] | 7.13 in |
| height | 181 mm |
| width [in] | 5.51 in |

| | |
|------------|---------|
| width | 140 mm |
| depth [in] | 3.39 in |
| depth | 86 mm |

Connections

| | |
|---|------------------------------|
| arrangement of electrical connectors / for main current circuit | Front terminal |
| type of electrical connection / for main current circuit | on both sides nut keeper kit |
| type of connectable conductor cross-sections / for flat-bar terminal connection / minimum | 13 x 1 mm |
| type of connectable conductor cross-sections / for flat-bar terminal connection / maximum | 25 x 8 mm |
| design of the surface / of the connections / on the top of the switch (N, 1, 3, 5) | tin |
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6) | tin |

Auxiliary circuit

| | |
|--|---|
| number of CO contacts / for auxiliary contacts | 0 |
|--|---|

Accessories

| | |
|--|-----|
| product extension / optional / motor drive | Yes |
|--|-----|

Environmental conditions

| | |
|------------------------------------|--------|
| protection class IP / on the front | IP40 |
| ambient temperature | |
| • during operation / minimum | -25 °C |
| • during operation / maximum | 70 °C |
| • during storage / minimum | -40 °C |
| • during storage / maximum | 80 °C |

Environmental footprint

| | |
|--|-----------------|
| global warming potential [CO2 eq] / total | 61.814 kg |
| global warming potential [CO2 eq] / during manufacturing | 14.6 kg |
| global warming potential [CO2 eq] / during operation | 48.9 kg |
| global warming potential [CO2 eq] / after end of life | -2.2 kg |
| Siemens Eco Profile (SEP) | Siemens EcoTech |
| reference code / according to IEC 81346-2 | Q |

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[Confirmation](#)

General Product Approval EMV Test Certificates



[Miscellaneous](#)

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

Maritime application



[CCS \(China Classification Society\)](#)

other Dangerous goods Environment

[Miscellaneous](#)

[Miscellaneous](#)

[Confirmation](#)



[Transport Information](#)

[Environmental Confirmations](#)



[Environmental Confirmations](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2040-8JQ42-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2040-8JQ42-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2040-8JQ42-0AA0

CAX-Online-Generator


<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>



last modified:

5/25/2025

