



Main

| | |
|--|---|
| Range | TeSys |
| Product name | TeSys LE |
| Device short name | LE4D |
| Product or component type | Enclosed DOL starter |
| Device application | Standard |
| Material | Polycarbonate |
| Utilisation category | AC-3 |
| Device composition | Thermal overload relay ordered separately Contactor Fuse disconnecter |
| [Ie] rated operational current | 12 A AC-3 |
| Motor power kW | 3 kW at 220/230 V AC 50/60 Hz 7.5 kW at 500 V AC 50/60 Hz 5.5 kW at 380/400 V AC 50/60 Hz 5.5 kW at 415 V AC 50/60 Hz 5.5 kW at 440 V AC 50/60 Hz |
| [Uc] control circuit voltage | 400 V AC 50/60 Hz |
| [Ithe] conventional enclosed thermal current | 12 A |
| Associated fuse rating | 16 A 10 x 38 mm aM |
| Control type | Push-button start green I Push-button stop/reset red O |

Complementary

| | |
|--------------------|--|
| Cable entry number | 2 ISO20 top 2 ISO25 top 2 ISO32 top 2 ISO40 top 2 ISO20 bottom 2 ISO25 bottom 2 ISO32 bottom 2 ISO40 bottom |
|--------------------|--|

| | |
|------------|----------|
| Width | 186 mm |
| Height | 330 mm |
| Depth | 175.5 mm |
| Net weight | 1.96 kg |

Environment

| | |
|---------------------------------------|------------------------------|
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 60529 |
| Standards | IEC 60947-4-1 |
| Ambient air temperature for operation | -5...40 °C |
| Environmental characteristic | Standard environment |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|