

# Thyristor Module

$$V_{RRM} = 2 \times 1600 \text{ V}$$

$$I_{TAV} = 60 \text{ A}$$

$$V_T = 1.24 \text{ V}$$

Phase leg

Part number

**MCC56-16io1B**



Backside: isolated

 E72873



## Features / Advantages:

- Thyristor for line frequency
- Planar passivated chip
- Long-term stability
- Direct Copper Bonded Al<sub>2</sub>O<sub>3</sub>-ceramic

## Applications:

- Line rectifying 50/60 Hz
- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control

## Package: TO-240AA

- Isolation Voltage: 3600 V~
- Industry standard outline
- RoHS compliant
- Soldering pins for PCB mounting
- Base plate: DCB ceramic
- Reduced weight
- Advanced power cycling

## Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).




| Thyristor      |                                                      |                                                                                                                                                                                                        |                                | Ratings |      |      |                   |
|----------------|------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|---------|------|------|-------------------|
| Symbol         | Definition                                           | Conditions                                                                                                                                                                                             |                                | min.    | typ. | max. | Unit              |
| $V_{RSM/DSM}$  | max. non-repetitive reverse/forward blocking voltage | $T_{VJ} = 25^{\circ}\text{C}$                                                                                                                                                                          |                                |         |      | 1700 | V                 |
| $V_{RRM/DRM}$  | max. repetitive reverse/forward blocking voltage     | $T_{VJ} = 25^{\circ}\text{C}$                                                                                                                                                                          |                                |         |      | 1600 | V                 |
| $I_{R/D}$      | reverse current, drain current                       | $V_{R/D} = 1600\text{ V}$                                                                                                                                                                              | $T_{VJ} = 25^{\circ}\text{C}$  |         |      | 200  | $\mu\text{A}$     |
|                |                                                      | $V_{R/D} = 1600\text{ V}$                                                                                                                                                                              | $T_{VJ} = 125^{\circ}\text{C}$ |         |      | 5    | mA                |
| $V_T$          | forward voltage drop                                 | $I_T = 100\text{ A}$                                                                                                                                                                                   | $T_{VJ} = 25^{\circ}\text{C}$  |         |      | 1.26 | V                 |
|                |                                                      | $I_T = 200\text{ A}$                                                                                                                                                                                   |                                |         |      | 1.57 | V                 |
|                |                                                      | $I_T = 100\text{ A}$                                                                                                                                                                                   | $T_{VJ} = 125^{\circ}\text{C}$ |         |      | 1.24 | V                 |
|                |                                                      | $I_T = 200\text{ A}$                                                                                                                                                                                   |                                |         |      | 1.62 | V                 |
| $I_{TAV}$      | average forward current                              | $T_C = 85^{\circ}\text{C}$                                                                                                                                                                             | $T_{VJ} = 125^{\circ}\text{C}$ |         |      | 60   | A                 |
| $I_{T(RMS)}$   | RMS forward current                                  | 180° sine                                                                                                                                                                                              |                                |         |      | 94   | A                 |
| $V_{T0}$       | threshold voltage                                    | for power loss calculation only                                                                                                                                                                        | $T_{VJ} = 125^{\circ}\text{C}$ |         |      | 0.85 | V                 |
| $r_T$          | slope resistance                                     |                                                                                                                                                                                                        |                                |         |      | 3.7  | m $\Omega$        |
| $R_{thJC}$     | thermal resistance junction to case                  |                                                                                                                                                                                                        |                                |         |      | 0.45 | K/W               |
| $R_{thCH}$     | thermal resistance case to heatsink                  |                                                                                                                                                                                                        |                                |         | 0.20 |      | K/W               |
| $P_{tot}$      | total power dissipation                              |                                                                                                                                                                                                        | $T_C = 25^{\circ}\text{C}$     |         |      | 222  | W                 |
| $I_{TSM}$      | max. forward surge current                           | $t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$                                                                                                                                                       | $T_{VJ} = 45^{\circ}\text{C}$  |         |      | 1.50 | kA                |
|                |                                                      | $t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$                                                                                                                                                      | $V_R = 0\text{ V}$             |         |      | 1.62 | kA                |
|                |                                                      | $t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$                                                                                                                                                       | $T_{VJ} = 125^{\circ}\text{C}$ |         |      | 1.28 | kA                |
|                |                                                      | $t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$                                                                                                                                                      | $V_R = 0\text{ V}$             |         |      | 1.38 | kA                |
| $I^2t$         | value for fusing                                     | $t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$                                                                                                                                                       | $T_{VJ} = 45^{\circ}\text{C}$  |         |      | 11.3 | kA <sup>2</sup> s |
|                |                                                      | $t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$                                                                                                                                                      | $V_R = 0\text{ V}$             |         |      | 10.9 | kA <sup>2</sup> s |
|                |                                                      | $t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$                                                                                                                                                       | $T_{VJ} = 125^{\circ}\text{C}$ |         |      | 8.13 | kA <sup>2</sup> s |
|                |                                                      | $t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$                                                                                                                                                      | $V_R = 0\text{ V}$             |         |      | 7.87 | kA <sup>2</sup> s |
| $C_J$          | junction capacitance                                 | $V_R = 400\text{ V}$ $f = 1\text{ MHz}$                                                                                                                                                                | $T_{VJ} = 25^{\circ}\text{C}$  |         | 74   |      | pF                |
| $P_{GM}$       | max. gate power dissipation                          | $t_p = 30\text{ }\mu\text{s}$                                                                                                                                                                          | $T_C = 125^{\circ}\text{C}$    |         |      | 10   | W                 |
|                |                                                      | $t_p = 300\text{ }\mu\text{s}$                                                                                                                                                                         |                                |         |      | 5    | W                 |
| $P_{GAV}$      | average gate power dissipation                       |                                                                                                                                                                                                        |                                |         |      | 0.5  | W                 |
| $(di/dt)_{cr}$ | critical rate of rise of current                     | $T_{VJ} = 125^{\circ}\text{C}; f = 50\text{ Hz}$ repetitive, $I_T = 150\text{ A}$                                                                                                                      |                                |         |      | 150  | A/ $\mu\text{s}$  |
|                |                                                      | $t_p = 200\text{ }\mu\text{s}; di_G/dt = 0.45\text{ A}/\mu\text{s};$<br>$I_G = 0.45\text{ A}; V = \frac{2}{3} V_{DRM}$ non-repet., $I_T = 60\text{ A}$                                                 |                                |         |      | 500  | A/ $\mu\text{s}$  |
| $(dv/dt)_{cr}$ | critical rate of rise of voltage                     | $V = \frac{2}{3} V_{DRM}$                                                                                                                                                                              | $T_{VJ} = 125^{\circ}\text{C}$ |         |      | 1000 | V/ $\mu\text{s}$  |
|                |                                                      | $R_{GK} = \infty$ ; method 1 (linear voltage rise)                                                                                                                                                     |                                |         |      |      |                   |
| $V_{GT}$       | gate trigger voltage                                 | $V_D = 6\text{ V}$                                                                                                                                                                                     | $T_{VJ} = 25^{\circ}\text{C}$  |         |      | 1.5  | V                 |
|                |                                                      |                                                                                                                                                                                                        | $T_{VJ} = -40^{\circ}\text{C}$ |         |      | 1.6  | V                 |
| $I_{GT}$       | gate trigger current                                 | $V_D = 6\text{ V}$                                                                                                                                                                                     | $T_{VJ} = 25^{\circ}\text{C}$  |         |      | 100  | mA                |
|                |                                                      |                                                                                                                                                                                                        | $T_{VJ} = -40^{\circ}\text{C}$ |         |      | 200  | mA                |
| $V_{GD}$       | gate non-trigger voltage                             | $V_D = \frac{2}{3} V_{DRM}$                                                                                                                                                                            | $T_{VJ} = 125^{\circ}\text{C}$ |         |      | 0.2  | V                 |
| $I_{GD}$       | gate non-trigger current                             |                                                                                                                                                                                                        |                                |         |      | 10   | mA                |
| $I_L$          | latching current                                     | $t_p = 10\text{ }\mu\text{s}$                                                                                                                                                                          | $T_{VJ} = 25^{\circ}\text{C}$  |         |      | 450  | mA                |
|                |                                                      | $I_G = 0.45\text{ A}; di_G/dt = 0.45\text{ A}/\mu\text{s}$                                                                                                                                             |                                |         |      |      |                   |
| $I_H$          | holding current                                      | $V_D = 6\text{ V}$ $R_{GK} = \infty$                                                                                                                                                                   | $T_{VJ} = 25^{\circ}\text{C}$  |         |      | 200  | mA                |
| $t_{gd}$       | gate controlled delay time                           | $V_D = \frac{1}{2} V_{DRM}$                                                                                                                                                                            | $T_{VJ} = 25^{\circ}\text{C}$  |         |      | 2    | $\mu\text{s}$     |
|                |                                                      | $I_G = 0.45\text{ A}; di_G/dt = 0.45\text{ A}/\mu\text{s}$                                                                                                                                             |                                |         |      |      |                   |
| $t_q$          | turn-off time                                        | $V_R = 100\text{ V}; I_T = 150\text{ A}; V = \frac{2}{3} V_{DRM}$ $T_{VJ} = 100^{\circ}\text{C}$<br>$di/dt = 10\text{ A}/\mu\text{s}$ $dv/dt = 20\text{ V}/\mu\text{s}$ $t_p = 200\text{ }\mu\text{s}$ |                                |         | 150  |      | $\mu\text{s}$     |

| Package TO-240AA |                                                              |                      |                                     | Ratings |      |      |      |
|------------------|--------------------------------------------------------------|----------------------|-------------------------------------|---------|------|------|------|
| Symbol           | Definition                                                   | Conditions           |                                     | min.    | typ. | max. | Unit |
| $I_{RMS}$        | RMS current                                                  | per terminal         |                                     |         |      | 200  | A    |
| $T_{VJ}$         | virtual junction temperature                                 |                      |                                     | -40     |      | 125  | °C   |
| $T_{op}$         | operation temperature                                        |                      |                                     | -40     |      | 100  | °C   |
| $T_{stg}$        | storage temperature                                          |                      |                                     | -40     |      | 125  | °C   |
| <b>Weight</b>    |                                                              |                      |                                     |         | 81   |      | g    |
| $M_D$            | mounting torque                                              |                      |                                     | 2.5     |      | 4    | Nm   |
| $M_T$            | terminal torque                                              |                      |                                     | 2.5     |      | 4    | Nm   |
| $d_{Spp/App}$    | creepage distance on surface   striking distance through air | terminal to terminal | 13.0                                | 9.7     |      |      | mm   |
| $d_{Spb/Apb}$    |                                                              | terminal to backside | 16.0                                | 16.0    |      |      | mm   |
| $V_{ISOL}$       | isolation voltage                                            | t = 1 second         | 50/60 Hz, RMS; $I_{ISOL} \leq 1$ mA | 3600    |      |      | V    |
|                  |                                                              | t = 1 minute         |                                     | 3000    |      |      | V    |



| Ordering | Ordering Number | Marking on Product | Delivery Mode | Quantity | Code No. |
|----------|-----------------|--------------------|---------------|----------|----------|
| Standard | MCC56-16io1B    | MCC56-16io1B       | Box           | 36       | 452769   |


| Similar Part  | Package     | Voltage class |
|---------------|-------------|---------------|
| MCMA65P1600TA | TO-240AA-1B | 1600          |
| MCMA85P1600TA | TO-240AA-1B | 1600          |

| Equivalent Circuits for Simulation                                                  |                    |           | * on die level | $T_{VJ} = 125^{\circ}\text{C}$ |
|-------------------------------------------------------------------------------------|--------------------|-----------|----------------|--------------------------------|
|  |                    | Thyristor |                |                                |
| $V_{0\max}$                                                                         | threshold voltage  | 0.85      |                | V                              |
| $R_{0\max}$                                                                         | slope resistance * | 2.5       |                | mΩ                             |

Technical drawing of a 5-pin DIN connector. The drawing shows the front and side views with the following dimensions and labels:

- Overall length:  $92 \pm 0.5$
- Distance from front face to center of pin 1:  $80 \pm 0.3$
- Pin 1 thread: M5
- Pin 1 diameter:  $5.5 \pm 0.1$
- Pin 1 height:  $10 \pm 0.1$
- Pin 1 offset:  $14.8$
- Pin 1 offset:  $20.8 \pm 0.25$
- Pin 2 diameter:  $4.4$
- Pin 2 height:  $5$
- Pin 2 offset:  $4.4$
- Pin 3 diameter:  $4.4$
- Pin 3 height:  $5$
- Pin 3 offset:  $4.4$
- Pin 4 diameter:  $4.4$
- Pin 4 height:  $5$
- Pin 4 offset:  $4.4$
- Pin 5 diameter:  $4.4$
- Pin 5 height:  $5$
- Pin 5 offset:  $4.4$
- Pin 6 diameter:  $4.4$
- Pin 6 height:  $5$
- Pin 6 offset:  $4.4$
- Pin 7 diameter:  $4.4$
- Pin 7 height:  $5$
- Pin 7 offset:  $4.4$
- Pin 8 diameter:  $4.4$
- Pin 8 height:  $5$
- Pin 8 offset:  $4.4$
- Pin 9 diameter:  $4.4$
- Pin 9 height:  $5$
- Pin 9 offset:  $4.4$
- Pin 10 diameter:  $4.4$
- Pin 10 height:  $5$
- Pin 10 offset:  $4.4$
- Pin 11 diameter:  $4.4$
- Pin 11 height:  $5$
- Pin 11 offset:  $4.4$
- Pin 12 diameter:  $4.4$
- Pin 12 height:  $5$
- Pin 12 offset:  $4.4$
- Pin 13 diameter:  $4.4$
- Pin 13 height:  $5$
- Pin 13 offset:  $4.4$
- Pin 14 diameter:  $4.4$
- Pin 14 height:  $5$
- Pin 14 offset:  $4.4$
- Pin 15 diameter:  $4.4$
- Pin 15 height:  $5$
- Pin 15 offset:  $4.4$
- Pin 16 diameter:  $4.4$
- Pin 16 height:  $5$
- Pin 16 offset:  $4.4$
- Pin 17 diameter:  $4.4$
- Pin 17 height:  $5$
- Pin 17 offset:  $4.4$
- Pin 18 diameter:  $4.4$
- Pin 18 height:  $5$
- Pin 18 offset:  $4.4$
- Pin 19 diameter:  $4.4$
- Pin 19 height:  $5$
- Pin 19 offset:  $4.4$
- Pin 20 diameter:  $4.4$
- Pin 20 height:  $5$
- Pin 20 offset:  $4.4$
- Pin 21 diameter:  $4.4$
- Pin 21 height:  $5$
- Pin 21 offset:  $4.4$
- Pin 22 diameter:  $4.4$
- Pin 22 height:  $5$
- Pin 22 offset:  $4.4$
- Pin 23 diameter:  $4.4$
- Pin 23 height:  $5$
- Pin 23 offset:  $4.4$
- Pin 24 diameter:  $4.4$
- Pin 24 height:  $5$
- Pin 24 offset:  $4.4$
- Pin 25 diameter:  $4.4$
- Pin 25 height:  $5$
- Pin 25 offset:  $4.4$
- Pin 26 diameter:  $4.4$
- Pin 26 height:  $5$
- Pin 26 offset:  $4.4$
- Pin 27 diameter:  $4.4$
- Pin 27 height:  $5$
- Pin 27 offset:  $4.4$
- Pin 28 diameter:  $4.4$
- Pin 28 height:  $5$
- Pin 28 offset:  $4.4$
- Pin 29 diameter:  $4.4$
- Pin 29 height:  $5$
- Pin 29 offset:  $4.4$
- Pin 30 diameter:  $4.4$
- Pin 30 height:  $5$
- Pin 30 offset:  $4.4$
- Pin 31 diameter:  $4.4$
- Pin 31 height:  $5$
- Pin 31 offset:  $4.4$
- Pin 32 diameter:  $4.4$
- Pin 32 height:  $5$
- Pin 32 offset:  $4.4$
- Pin 33 diameter:  $4.4$
- Pin 33 height:  $5$
- Pin 33 offset:  $4.4$
- Pin 34 diameter:  $4.4$
- Pin 34 height:  $5$
- Pin 34 offset:  $4.4$
- Pin 35 diameter:  $4.4$
- Pin 35 height:  $5$
- Pin 35 offset:  $4.4$
- Pin 36 diameter:  $4.4$
- Pin 36 height:  $5$
- Pin 36 offset:  $4.4$
- Pin 37 diameter:  $4.4$
- Pin 37 height:  $5$
- Pin 37 offset:  $4.4$
- Pin 38 diameter:  $4.4$
- Pin 38 height:  $5$
- Pin 38 offset:  $4.4$
- Pin 39 diameter:  $4.4$
- Pin 39 height:  $5$
- Pin 39 offset:  $4.4$
- Pin 40 diameter:  $4.4$
- Pin 40 height:  $5$
- Pin 40 offset:  $4.4$
- Pin 41 diameter:  $4.4$
- Pin 41 height:  $5$
- Pin 41 offset:  $4.4$
- Pin 42 diameter:  $4.4$
- Pin 42 height:  $5$
- Pin 42 offset:  $4.4$
- Pin 43 diameter:  $4.4$
- Pin 43 height:  $5$
- Pin 43 offset:  $4.4$
- Pin 44 diameter:  $4.4$
- Pin 44 height:  $5$
- Pin 44 offset:  $4.4$
- Pin 45 diameter:  $4.4$
- Pin 45 height:  $5$
- Pin 45 offset:  $4.4$
- Pin 46 diameter:  $4.4$
- Pin 46 height:  $5$
- Pin 46 offset:  $4.4$
- Pin 47 diameter:  $4.4$
- Pin 47 height:  $5$
- Pin 47 offset:  $4.4$
- Pin 48 diameter:  $4.4$
- Pin 48 height:  $5$
- Pin 48 offset:  $4.4$
- Pin 49 diameter:  $4.4$
- Pin 49 height:  $5$
- Pin 49 offset:  $4.4$
- Pin 50 diameter:  $4.4$
- Pin 50 height:  $5$
- Pin 50 offset:  $4.4$
- Pin 51 diameter:  $4.4$
- Pin 51 height:  $5$
- Pin 51 offset:  $4.4$
- Pin 52 diameter:  $4.4$
- Pin 52 height:  $5$
- Pin 52 offset:  $4.4$
- Pin 53 diameter:  $4.4$
- Pin 53 height:  $5$
- Pin 53 offset:  $4.4$
- Pin 54 diameter:  $4.4$
- Pin 54 height:  $5$
- Pin 54 offset:  $4.4$
- Pin 55 diameter:  $4.4$
- Pin 55 height:  $5$
- Pin 55 offset:  $4.4$
- Pin 56 diameter:  $4.4$
- Pin 56 height:  $5$
- Pin 56 offset:  $4.4$
- Pin 57 diameter:  $4.4$
- Pin 57 height:  $5$
- Pin 57 offset:  $4.4$
- Pin 58 diameter:  $4.4$
- Pin 58 height:  $5$
- Pin 58 offset:  $4.4$
- Pin 59 diameter:  $4.4$
- Pin 59 height:  $5$
- Pin 59 offset:  $4.4$
- Pin 60 diameter:  $4.4$
- Pin 60 height:  $5$
- Pin 60 offset:  $4.4$
- Pin 61 diameter:  $4.4$
- Pin 61 height:  $5$
- Pin 61 offset:  $4.4$
- Pin 62 diameter:  $4.4$
- Pin 62 height:  $5$
- Pin 62 offset:  $4.4$
- Pin 63 diameter:  $4.4$
- Pin 63 height:  $5$
- Pin 63 offset:  $4.4$
- Pin 64 diameter:  $4.4$
- Pin 64 height:  $5$
- Pin 64 offset:  $4.4$
- Pin 65 diameter:  $4.4$
- Pin 65 height:  $5$
- Pin 65 offset:  $4.4$
- Pin 66 diameter:  $4.4$
- Pin 66 height:  $5$
- Pin 66 offset:  $4.4$
- Pin 67 diameter:  $4.4$
- Pin 67 height:  $5$
- Pin 67 offset:  $4.4$
- Pin 68 diameter:  $4.4$
- Pin 68 height:  $5$
- Pin 68 offset:  $4.4$
- Pin 69 diameter:  $4.4$

Type ZY 200L (L = Left for pin pair 4/5)  
Type ZY 200R (R = Right for pin pair 6/7) } UL 758, style 3751



## Thyristor




Fig. 1 Surge overload current  $I_{TSM}$ ,  
 $I_{FSM}$ : Crest value,  $t$ : duration




Fig. 2  $I^2dt$  versus time (1-10 ms)




Fig. 3 Max. forward current  
 at case temperature




Fig. 4 Power dissipation vs. on-state current & ambient temperature  
 (per thyristor or diode)




Fig. 5 Gate trigger characteristics



Fig. 6 Three phase rectifier bridge: Power dissipation versus direct  
 output current and ambient temperature




Fig. 7 Gate trigger delay time

## Thyristor




Fig. 8 Three phase AC-controller: Power dissipation versus RMS output current and ambient temperature




Fig. 9 Transient thermal impedance junction to case (per thyristor/diode)

$R_{thJC}$  for various conduction angles d:

| d    | $R_{thJC}$ [K/W] |
|------|------------------|
| DC   | 0.450            |
| 180° | 0.470            |
| 120° | 0.490            |
| 60°  | 0.505            |
| 30°  | 0.520            |

Constants for  $Z_{thJC}$  calculation:

| i | $R_{thi}$ [K/W] | $t_i$ [s] |
|---|-----------------|-----------|
| 1 | 0.014           | 0.0150    |
| 2 | 0.026           | 0.0095    |
| 3 | 0.410           | 0.1750    |




Fig. 10 Transient thermal impedance junction to heatsink (per thyristor/diode)

$R_{thJK}$  for various conduction angles d:

| d    | $R_{thJK}$ [K/W] |
|------|------------------|
| DC   | 0.650            |
| 180° | 0.670            |
| 120° | 0.690            |
| 60°  | 0.705            |
| 30°  | 0.720            |

Constants for  $Z_{thJK}$  calculation:

| i | $R_{thi}$ [K/W] | $t_i$ [s] |
|---|-----------------|-----------|
| 1 | 0.014           | 0.0150    |
| 2 | 0.026           | 0.0095    |
| 3 | 0.410           | 0.1750    |
| 4 | 0.200           | 0.6700    |