


circuit breaker VL160L without Electronic Trip Unit very high breaking capacity Icu=100kA/415V AC, 4-pole In=< 160A, rated current without auxiliary release with box terminals f. switching unit and Electronic Trip Unit

Weight	2.263 kg
Net Weight	2.263 kg

Approvals / Certificates



Environment	General Product Approval				
Environmental Conformations	Environmental Conformations			Confirmation	

Test Certificates

Test Certificates	other			
Special Test Certificate	Miscellaneous	Confirmation		Miscellaneous

Further information

- Information on the packaging**
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage**
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (catalogues, leaflets,...)**
<https://www.siemens.com/energy-automation>
- Industry Mall (Online ordering system)**
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2716-3AA43-0AA0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
<https://support.industry.siemens.com/cs/ww/en/ps/3VL2716-3AA43-0AA0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2716-3AA43-0AA0
- CAX-Online-Generator**
<https://www.siemens.com/cax>
- Characteristic curves**
[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified: 4/4/2025 

