


circuit breaker VL1250L very high breaking capacity Icu=100kA, 415V AC 4-pole, line protection trip unit LCD ETU42, LSIG In=1250A, rated current IR=500...1250A, overload protection, ISD=1.5 to 9xIR, II=10xIN short-circuit protection N protected with ground-fault protection without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	34.4 kg
Net Weight	34.4 kg

### Approvals / Certificates

Environment	General Product Approval				
<a href="#">Environmental Confirmations</a>	<a href="#">Environmental Confirmations</a>			<a href="#">Confirmation</a>	

Test Certificates	other	Dangerous goods			
<a href="#">Special Test Certificate</a>	<a href="#">Miscellaneous</a>	<a href="#">Confirmation</a>		<a href="#">Miscellaneous</a>	<a href="#">Transport Information</a>

### Further information

- Information on the packaging <https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage <https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (catalogues, leaflets,...) <https://www.siemens.com/energy-automation>
- Industry Mall (Online ordering system) <https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL7712-3UN46-0AA0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...) <https://support.industry.siemens.com/cs/ww/en/ps/3VL7712-3UN46-0AA0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) [https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL7712-3UN46-0AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL7712-3UN46-0AA0)
- CAx-Online-Generator <https://www.siemens.com/cax>
- Characteristic curves [https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified: 11/24/2025 

