




circuit breaker VL160X N standard breaking capacity Icu=55kA, 415V AC 3-pole, line protection Trip Unit TM, LI In=63A, rated current Ir=50...63A, overload prot. II=600A, short-circuit prot. Undervoltage release 220...250 V DC without auxiliary/alarm switch, spare part product only for replacement purposes

| | |
|------------|------|
| Weight | 2 kg |
| Net Weight | 2 kg |


Approvals / Certificates

| Environment | General Product Approval | | | | |
|---|---|---|---|------------------------------|---|
| Environmental Conformations | Environmental Conformations |  |  | Confirmation |  |

| Test Certificates | other | | | | |
|--|-------------------------------|------------------------------|---|-------------------------------|--|
| Special Test Certificate | Miscellaneous | Confirmation |  | Miscellaneous | |

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (catalogues, leaflets,...)
<https://www.siemens.com/energy-automation>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL1706-1DD33-2SA0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VL1706-1DD33-2SA0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL1706-1DD33-2SA0
- CAX-Online-Generator
<https://www.siemens.com/cax>
- Characteristic curves
[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified: 4/1/2026 

