



Figure similar

accessory for VL630; VL800 motorized operating mechanism 220-250V AC/DC for MCCB greater than, equal to \*E02\*01\* spare part product only for replacement purposes

Model	
product brand name	SETRON
product designation	Motorized operating mechanism
design of the product	Accessories for VL630; VL800
type of the driving mechanism	motorized operating mechanism
General technical data	
operating frequency maximum	120 1/h
Voltage	
fuse protection type for external auxiliary power supply required	NEOZED fuse (gL/gG): 2 A / miniature circuit breaker, C char.: 2 A
operating range factor control supply voltage rated value	
• at DC initial value	0.85
• at DC full-scale value	1.1
• at AC at 50 Hz initial value	0.85
• at AC at 50 Hz full-scale value	1.1
• at AC at 60 Hz initial value	0.85
• at AC at 60 Hz full-scale value	1.1
Protection class	
protection class IP	IP30
Control current	
operating apparent power	100 VA
control supply voltage	
• at DC rated value minimum	250 V
• at DC rated value maximum	220 V
• at AC at 50 Hz rated value minimum	220 V
• at AC at 50 Hz rated value maximum	250 V
• at AC at 60 Hz rated value minimum	220 V
• at AC at 60 Hz rated value maximum	250 V
Accessories	
accessories	Accessories for VL630; VL800
pulse duration minimum	50 ms
Connections	
stripped length	9 mm
connectable conductor cross-section solid	
• minimum	1.5 mm <sup>2</sup>
• maximum	1.5 mm <sup>2</sup>
connectable conductor cross-section stranded	
• minimum	1.5 mm <sup>2</sup>
• maximum	1.5 mm <sup>2</sup>

<b>connectable conductor cross-section finely stranded with core end processing</b>	
<ul style="list-style-type: none"> <li>• minimum</li> </ul>	1.5 mm <sup>2</sup>
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	1.5 mm <sup>2</sup>

### Mechanical Design

<b>height</b>	168.9 mm
<b>width</b>	190 mm
<b>depth</b>	182 mm
<b>Net Weight</b>	2.332 kg

### Environmental conditions

<b>ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>• minimum</li> </ul>	-25 °C
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	70 °C
<b>ambient temperature during storage</b>	
<ul style="list-style-type: none"> <li>• minimum</li> </ul>	-40 °C
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	80 °C

### Certificates

<b>reference code according to IEC 81346-2</b>	M
--	---

### Approvals Certificates

Environment	General Product Approval	Test Certificates
<a href="#">Environmental Conformations</a>		<a href="#">Confirmation</a>
<a href="#">Environmental Conformations</a>		<a href="#">Special Test Certificate</a>

### Maritime application other

	<a href="#">Confirmation</a>		<a href="#">Miscellaneous</a>
---	------------------------------	---	-------------------------------

### Further information

- Information on the packaging**  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage**  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (Catalogs, Brochures,...)**  
<https://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)**  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL9600-3ME10>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**  
<https://support.industry.siemens.com/cs/ww/en/ps/3VL9600-3ME10>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**  
[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL9600-3ME10](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL9600-3ME10)
- CAX-Online-Generator**  
<https://www.siemens.com/cax>
- Tender specifications**  
<https://www.siemens.com/specifications>
- Characteristic curves**  
[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

last modified: 5/30/2026 

