SIEMENS

Data sheet 3VL1712-2DD36-0AD1

circuit breaker VL160X H high breaking capacity Icu=70kA, 415V AC 3-pole, line protection Trip Unit TM, LI In=125A, rated current Ir=125A, overload protection II=1000A, short-circuit prot. with screw terminals without auxiliary release Auxiliary/alarm switch mounting kit 2 AUX (1 NO+1 NC)+1 AS (1 NO)

Weight	2.082 kg
Net Weight	2.082 kg

Approvals / Certificates

Environment		General Product Approval		Test Certificates
Environmental Confirmations	Environmental Confirmations	EAC	Confirmation	Special Test Certificate

other

Miscellaneous	Confirmation	产品合格 QC PASS	Miscellaneous

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (catalogues, leaflets,...)
https://www.siemens.com/energy-automation
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL1712-2DD36-0AD1
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL1712-2DD36-0AD1
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL1712-2DD36-0AD1
CAx-Online-Generator
https://www.siemens.com/cax
Characteristic curves
https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod__no>



last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens