



circuit breaker VL160X N standard breaking capacity I<sub>cu</sub>=55kA, 415V AC 4-pole, line protection Trip Unit TM, LI I<sub>n</sub>=25A, rated current I<sub>r</sub>=25A, overload protection I<sub>l</sub>=300A, short-circuit prot. N unprotected with screw terminals without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	2.639 kg
Net Weight	2.639 kg

### Approvals / Certificates

Environment	General Product Approval	Test Certificates
<a href="#">Environmental Confirmations</a> 	<a href="#">Confirmation</a> 	<a href="#">Special Test Certificate</a>

### other

<a href="#">Miscellaneous</a>	<a href="#">Confirmation</a>		<a href="#">Miscellaneous</a>
-------------------------------	------------------------------	--	-------------------------------

### Further information

- Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (catalogues, leaflets,...)  
<https://www.siemens.com/energy-automation>
- Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL1725-1EH46-0AA0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/3VL1725-1EH46-0AA0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)  
[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL1725-1EH46-0AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL1725-1EH46-0AA0)
- CAx-Online-Generator  
<https://www.siemens.com/cax>
- Characteristic curves  
[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified: 11/24/2025 

