



circuit breaker VL160L very high breaking capacity Icu=100kA, 415V AC 4-pole, line protection Trip Unit TM, LI In=50A, rated current Ir=40...50A, overload prot. II=300...600A, short-circuit protection, N unprotected N unprotected Shunt release 380...600 V AC Auxiliary switch mounting kit 2 AUX (1 NO + 1 NC)

Weight	3 kg
Net Weight	3 kg

### Approvals / Certificates

Environment	General Product Approval
-------------	--------------------------

[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)



[Confirmation](#)



Test Certificates	other
-------------------	-------

[Special Test Certifi-  
cate](#)

[Miscellaneous](#)

[Confirmation](#)



[Miscellaneous](#)

### Further information

#### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

#### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

#### Information- and Downloadcenter (catalogues, leaflets,...)

<https://www.siemens.com/energy-automation>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2705-3EJ43-8VB1>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL2705-3EJ43-8VB1>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL2705-3EJ43-8VB1](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2705-3EJ43-8VB1)

#### CAX-Online-Generator

<https://www.siemens.com/cax>

#### Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified:

3/10/2026

