



circuit breaker VL160L very high breaking capacity Icu=100kA, 415V AC 4-pole, line protection Trip Unit TM, LI In=50A, rated current Ir=40...50A, overload prot. II=300...600A, short-circuit protection, N protected N protected without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	3.153 kg
Net Weight	3.153 kg

Approvals / Certificates

Environment	General Product Approval				
Environmental Confirmations	Environmental Confirmations			Confirmation	

Test Certificates	other			
Special Test Certificate	Miscellaneous	Confirmation		Miscellaneous

Further information

- Information on the packaging**
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage**
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (catalogues, leaflets,...)**
<https://www.siemens.com/energy-automation>
- Industry Mall (Online ordering system)**
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2705-3EM43-0AA0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
<https://support.industry.siemens.com/cs/ww/en/ps/3VL2705-3EM43-0AA0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2705-3EM43-0AA0
- CAx-Online-Generator**
<https://www.siemens.com/cax>
- Characteristic curves**
[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified: 11/24/2025 

