



circuit breaker VL160L very high breaking capacity Icu=100kA, 415V AC 3-pole, line protection Trip Unit TM, LI In=63A, rated current IR=50...63A, overload protection, II=300...600A, short-circuit protection Undervoltage release 220...250 V DC Auxiliary switch mounting kit 2 AUX (1 NO + 1 NC)

Weight	2.2 kg
Net Weight	2.2 kg

Approvals / Certificates

Environment	General Product Approval
-------------	--------------------------

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)



[Confirmation](#)



Test Certificates	other
-------------------	-------

[Special Test Certifi-
cate](#)

[Miscellaneous](#)

[Confirmation](#)



[Miscellaneous](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (catalogues, leaflets,...)

<https://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2706-3DC33-2SB1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL2706-3DC33-2SB1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2706-3DC33-2SB1

CAX-Online-Generator

<https://www.siemens.com/cax>

Characteristic curves

https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>



last modified:

11/24/2025

