



circuit breaker VL160N standard breaking capacity Icu=55kA, 415V AC 3-pole, line protection Trip Unit TM, LI In=80A, rated current IR=63...80A, overload protection, II=400...800A, short-circuit protection with screw terminals Undervoltage release 220...250 V AC without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	2.2 kg
Net Weight	2.2 kg

### Approvals / Certificates

Environment	General Product Approval				
<a href="#">Environmental Confirmations</a>	<a href="#">Environmental Confirmations</a>			<a href="#">Confirmation</a>	

Test Certificates	other			
<a href="#">Special Test Certificate</a>	<a href="#">Miscellaneous</a>	<a href="#">Confirmation</a>		<a href="#">Miscellaneous</a>

### Further information

- Information on the packaging**  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage**  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (catalogues, leaflets,...)**  
<https://www.siemens.com/energy-automation>
- Industry Mall (Online ordering system)**  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2708-1DC36-2HA0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**  
<https://support.industry.siemens.com/cs/ww/en/ps/3VL2708-1DC36-2HA0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**  
[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL2708-1DC36-2HA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2708-1DC36-2HA0)
- CAx-Online-Generator**  
<https://www.siemens.com/cax>
- Characteristic curves**  
[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified: 3/10/2026 

